

SAFETY IN MINES RESEARCH ADVISORY COMMITTEE

SIMRAC

Final Project Report

Title: RELIABLE COST EFFECTIVE TECHNIQUE FOR IN-SITU
GROUND STRESS MEASUREMENTS IN DEEP GOLD
MINES

Author/s: T R STACEY

Research
Agency: STEFFEN, ROBERTSON AND KIRSTEN

Project No: GAP 220

Date: JULY 1995

Project No : GAP 220

**RELIABLE COST EFFECTIVE TECHNIQUE
FOR IN-SITE GROUND STRESS MEASUREMENTS
IN DEEP GOLD MINES**

Prepared by :

T R Stacey*

10 July 1995

*Steffen, Robertson and Kirsten, Consulting Engineers

CONTENTS

	Page
EXECUTIVE SUMMARY	
1 INTRODUCTION	1
2 REVIEW OF METHODS OF IN SITU STRESS MEASUREMENT	2
2.1 Borehole-based methods of in situ stress measurement	3
2.1.1 Borehole deformation and strain	3
2.1.1.1 Measurement of borehole deformation	3
2.1.1.2 Strain measurement on the borehole end	6
2.1.1.3 Strain measurement on the wall of the borehole	9
2.1.2 Borehole inclusion stressmeters	13
2.1.3 Hydraulic fracturing method	15
2.1.4 Other borehole methods	18
2.2 The flat jack stress measurement technique	18
2.3 Back analysis of in situ stresses from field measurements	21
2.4 Borehole observational methods	22
2.5 Other methods	23
3 APPLICABILITY OF EXISTING METHODS OF IN SITU STRESS MEASUREMENT TO DEEP LEVEL GOLD MINES	23
3.1 Borehole overcoring methods	24
3.2 Large diameter overcoring in a bored raise	27
3.3 Hydrofracturing	28
3.4 Back analysis from monitored deformations around excavations	29
3.5 Summary regarding the applicability of existing methods of in situ stress measurement	30
4 REQUIREMENTS FOR A RELIABLE COST EFFECTIVE TECHNIQUE FOR IN SITU STRESS MEASUREMENT IN DEEP GOLD MINES	31
5 CONCEPTUAL DEVELOPMENT OF A RELIABLE COST EFFECTIVE TECHNIQUE FOR GROUND STRESS MEASUREMENTS IN DEEP GOLD MINES	33
5.1 Stress analyses of the concept	36
5.1.1 Two-dimensional elastic analyses	38
5.1.2 Two-dimensional analyses allowing rock failure to develop	38
5.1.3 Three-dimensional stress analyses	45
6 CONCLUSIONS AND RECOMMENDATIONS	45
7 REFERENCES AND BIBLIOGRAPHY	47
APPENDIX A	77

LIST OF FIGURES

Figure		Page
Figure 1	Application of borehole deformation meter	5
Figure 2	Solid inclusion gauge (after Blackwood,1977)	7
Figure 3	CSIR Doorstopper Strain Cell System	8
Figure 4	CSIR and CSIRO Triaxial Strain Cell System of in situ stress measurement	11
Figure 5	Interfels Borehole Slotter System of in situ stress measurement	14
Figure 6	Hydraulic Fracturing Method of in situ stress measurement	16
Figure 7	Flat Jack Method of in situ stress measurement	20
Figure 8	Variation of results for overcore methods compared with bored raise overcoring and back analysis technique	25
Figure 9	Conceptual method of in situ measurement applicable to deep gold mines	34
Figure 10	Perspective view of the proposed method	37
Figure 11	Vertical displacements as a result of the drilling of the third hole	39
Figure 12	Horizontal displacements as a result of the drilling of the third hole	40
Figure 13	Vertical displacements as a result of the drilling of the third hole: inclined stress field	41
Figure 14	Horizontal displacements as a result of the drilling of the third hole: inclined stress field	42
Figure 15	Vertical displacements as a result of the drilling of the third hole: strain softening model	43
Figure 16	Horizontal displacements as a result of the drilling of the third hole: strain softening model	44
Figure 17	Vertical displacements in a vertical plane along the axis of the first borehole, as a result of the drilling of the third borehole	46

EXECUTIVE SUMMARY

The proposed Primary Output of this research project, as indicated in the proposal, is the following:

- a literature survey of existing methods of in-situ stress measurement including an evaluation of the applicability of these methods in the deep level gold mines.
- a theoretical feasibility study of a potential method, which will be cost effective and practical, and applicable to the gold mine situation.

A review of the extensive literature on the subject of in situ stress measurement has been carried out, and a substantial bibliography is included in the report. The majority of methods of in situ stress measurement which are available were immediately rejected as being inapplicable for the deep gold mines. Several methods were identified as having potential applicability from a technical viewpoint and were dealt with in more detail. These methods are:

- borehole overcoring methods, including the CSIR doorstopper strain cell, the CSIR triaxial strain cell, and the CSIRO HI cell
- large diameter overcoring in a bored raise
- hydrofracturing
- back analysis from monitored deformations around excavations.


It is considered that the applicability of these methods in the deep gold mines is poor. Reasons for this include their cost, their requirement for significant assistance from mines in terms of services and personnel, and their reliability in general and under the harsh conditions in the mines. Only two of the approaches are considered to have limited application. These are a simplified hydrofracture test, in which only the magnitude of the minimum principal stress is determined, and back analysis from monitored deformations, when suitable excavations are made for other purposes and economic monitoring can be used.

Based on the review of the available methods of in situ stress measurement, and experience of involvement in stress measurement programmes using numerous techniques, the following have been identified as requirements for a reliable, cost effective technique for in situ stress measurement in deep gold mines:


- the technique must be undemanding on the requirement for services and personnel provided by the mine.
- the technique should be low cost with regard to all aspects - cost of preparation, cost of installation, cost of instrumentation, cost per measurement, and economical in terms of time requirements.
- the technique should allow many measurements to be made in a single mining shift. This will allow the results to be treated statistically and therefore avoid localised effects.
- the technique should not be sensitive to high stress effects such as spalling and microcracking of the rock.
- the technique should be flexible. It should be possible to implement at very short notice, require a minimum of preparation, be possible to apply in excavations of limited size and non-restrictive location.
- the technique should preferably not require the retrieval of rock cores and laboratory testing to determine the deformation properties of the rock or rock mass.

Based on these requirements, an in situ stress measurement technique which will be practically applicable in the deep gold mines, has been developed conceptually. Referring to the figure on the following page, this method involves:

- a borehole-based system, using percussion boreholes drilled with a conventional jackhammer
- creating the enlargement, or stress/strain change, not by overcoring, but by drilling parallel, overlapping holes
- control of the direction of adjacent holes, and prevention of movement of drill chips into the measuring hole, by means of a special borehole guide
- measurement of deformation changes in the first borehole, as a result of the drilling of the third borehole, by means of a borehole deformation meter
- sequential deformation change measurements down the length of the borehole, alternately moving the deformation meter and advancing the third borehole
- measurements carried out in three different borehole orientations at each site to provide sufficient data for the complete state of stress to be determined
- calculation of the in situ stress field by back analysis of monitored deformations using an appropriate numerical stress analysis program.
- optimisation of results making use of the redundancy in number of data.



JOB No
213413



CONCEPTUAL METHOD OF IN SITU STRESS MEASUREMENT
APPLICABLE TO DEEP GOLD MINES

The theoretical feasibility of the method has been proved by carrying out two- and three-dimensional stress analyses. These showed that:

- deformations induced around the first borehole by the drilling of the third borehole are of sufficient magnitude to measure easily
- the effect on the deformations of failure around the boreholes due to overstress is probably less than the variations due to experimental errors and local rock material variations
- approximately 5 measurements per metre length of borehole can be carried out.

It is concluded that a method of in situ stress measurement, based on the percussion drilling of a set of three overlapping boreholes, and back analysing the in situ stresses from the measured deformations in the boreholes, has been developed in concept. By its very nature, being based on low cost drilling and deformation measuring operations, whose application is very flexible, the method will be cost effective. In concept, the method overcomes the disadvantages of most of the available methods of in situ stress measurement, and therefore should be reliable. It is also aimed at being specifically applicable under the conditions which occur in deep mines, and its feasibility has been proved theoretically.

In the SIMRAC proposal document it is stated that the primary output of the research project would be at feasibility level, and that further development would be required for the technique to be developed for routine use. It is recommended that this development should proceed, and several aspects are identified as needing development to ensure that the method can be applied practically:

- the development of a suitable drilling guide which can cope with variation in the straightness of the holes, some variation in the diameter of the holes, and "wedging" due to some closure of the holes, impact of the drill and packing of the drill chippings.
- development of a suitable deformation meter.
- development of the standard back analysis procedure. The approach, and an appropriate simple stress analysis program, need to be adapted for the specific in situ stress measurement application.

1 INTRODUCTION

Knowledge of the in situ state of stress in a rock mass is essential for the proper planning and design of mine layouts to optimise stability and safety of mining operations. The in situ stresses are essential boundary conditions for all design and analysis methods making use of stress analysis, and the use of incorrect boundary conditions will provide invalid design results which could be significant with regard to stability and safety.

The in situ state of stress in a rock mass can be determined by direct measurement, and there are numerous methods of measurement which are currently in use. A review of some of these methods is included in the following section. Although some measurements of in situ stress were carried out prior to 1950, significant research into methods of in situ stress measurement began in the 1950's and has continued to the present time. In South Africa, research in the 1950's and early 1960's led to the development of borehole strain cells for the measurement of both two- and three-dimensional states of stress. This work was completed in mid-1960, and at that stage South African expertise was probably the best available in the world. It is interesting to note that Leeman (1965), referring to some minor outstanding instrumentation problems, concluded, "Once this is achieved it can be said that the problem of measuring the stress in rock is, to all intents and purposes, 'licked'!" The requirement for the present research project clearly disputes this statement.

It is unfortunate that no significant research in the field of in situ stress measurements has been carried out in South Africa since that time, in spite of the fact that, in the past 30 years, mining has progressed to much greater depths, where stress conditions are even more critical. The consequence of this is that, whereas South Africa was a leader in the 1960's and 1970's, today most in situ stress measurements carried out internationally make use of non-South African technology. A further consequence is that techniques that are appropriate for the very high stress conditions in our deep level mines have not been developed.

This is some of the background to the present SIMRAC research project, the title of which is "Reliable cost effective technique for in-situ ground stress measurements in deep gold mines". A copy of the research proposal is contained in Appendix A for record purposes. The proposed Primary Output, as indicated in the proposal, is as follows:

- i) a literature survey of existing methods of in-situ stress measurement including an evaluation of the applicability of these methods in the deep level gold mines.
- ii) a theoretical feasibility study of a potential method, which will be cost effective and practical, and applicable to the gold mine situation.

More specifically, the output from the research project will include the following:

- a review of existing methods of in situ stress measurement
- identification of those methods which are possibly more appropriate in South African gold mines
- assessment of the applicability of these more appropriate methods, and identification of the advantages and disadvantages of each method
- definition of the requirements, both theoretical and practical, for in situ stress measurements in deep level mines
- based on these requirements, conceptual development of a reliable and cost-effective method of in situ stress measurement

REVIEW OF METHODS OF IN SITU STRESS MEASUREMENT

Significant reviews of methods of in situ rock stress measurement have been carried out previously by Leeman (1964a), Leeman (1964b), Obert (1967), and Leeman (1969a). A repetition of these exhaustive reviews of the literature is not considered to be appropriate for this SIMRAC research project. An extensive, but not exhaustive, bibliography of literature on in situ stress measurements is included in this report.

It is also not considered necessary to include details of stress-strain relationships and equations involved in the various methods of in situ stress measurement, since these are readily available in documents which will be referred to in the text. Instead, information from the previous reviews will be summarised, and particular attention will be paid to relevant methods which have been developed since the reviews were carried out.

Most of the methods of in situ stress measurement involve the observation of a change in deformation or stress resulting from a change in the geometry of an opening in the rock, and the subsequent calculation of the field stresses from those measured changes. Most of the methods are associated with boreholes as the "opening" in the rock mass.

2.1 Borehole-based methods of in situ stress measurement

With regard to measurement of changes in boreholes, there are methods which measure borehole deformation, borehole strain, borehole surface strain, and stress change.

2.1.1 Borehole deformation and strain

This group of methods is probably the most common type, and there is a variety of different methods based on the concept. In all of the methods, deformations or strains are measured, and stresses are calculated from these measured values by means of elastic theory. In all cases the closed form theoretical solution relating the elastic stresses and strains around the borehole or borehole end is known.

2.1.1.1 Measurement of borehole deformation

Borehole deformation meter


This instrument measures the change in diameter, at several several angular orientations, of the borehole as a result of the overcoring, and hence destressing, of the borehole. The practical procedure is as follows. A borehole is diamond core

drilled, at overcore size, to the required depth so that it is at a sufficient distance to be out of the stress concentrating influence of the excavation from which the hole is drilled. A smaller diameter pilot hole, coaxial with the initial hole, is then drilled into the end of the initial hole, and the deformation meter is placed in this pilot hole. The meter is then overcored, with changes in deformation of the borehole being measured during the overcoring process. The overcore is subsequently tested in the laboratory to determine its deformation properties, and the in situ stresses are calculated from the overcore deformation values using elastic theory. The application of the method is illustrated in Figure 1.


In a single hole the secondary principal stresses acting in a plane normal to the borehole axis may be determined. To determine the complete state of stress in the rock mass, measurements must be made in three differently orientated boreholes. Bonnechere and Cornet, 1977, describe a borehole deformation meter with the capability of measuring deformation change in the axial direction. Such an instrument can be used to determine the complete state of stress in a single borehole.

The most commonly used borehole deformation meter is the United States Bureau of Mines (USBM) deformation meter (Obert et al, 1962, Hooker et al, 1974)). The hole in which the instrument is installed is an EX hole (approximately 38 mm diameter), and the overcore typically has a diameter of 150 mm.


Application of the method requires high quality diamond core drilling, with associated equipment, facilities and services, using large diameter (150 mm) bits, and a special device for centring of the pilot hole. Success with the method is also dependent on good quality rock such that intact overcores at least 300 mm long can be obtained. The deformation meter can be used in wet conditions if it has been waterproofed. Since elastic theory is used for the calculation of the in situ stresses from the measured deformations, it is important that no failure of the rock occurs around the borehole which might lead to non-elastic behaviour.




a) BOREHOLE DRILLED TO THE DEPTH AT WHICH THE STRESS IS TO BE DETERMINED



b) PILOT BOREHOLE DRILLED INTO THE END OF THE BOREHOLE



c) DEFORMATION METER PLACED IN THE PILOT BOREHOLE



d) PILOT BOREHOLE OVERCORED AND STRAIN RELIEF MONITORED



JOB NO
213413

APPLICATION OF BOREHOLE DEFORMATION METER

FIG. NO
1

Solid inclusion gauges

A solid inclusion gauge, which contain wire resistance strain gauges to measure deformation across the axis of the borehole, has been developed by Blackwood (1977). The geometry of the strain gauges in this cell is shown in Figure 2.


The application is similar to the borehole deformation meter, but the solid inclusion unit is bonded into the pilot hole. The tolerance between the borehole and the outer diameter of the cell is important. After installation, the cell is overcored, with strain changes being monitored during overcoring.

Since there are sufficient strain relief components measured, the method allows the complete state of stress to be determined in a single borehole.

As with the deformation meter, diamond drilling equipment is a requirement. The bonding between the cell and the rock is critical, as was found by Rocha and Silverio (1969), and problems in this area led to the design of a new cell by LNEC. It is likely that this type of problem would be present in high stress conditions in which rock failure may occur and differential deformations would be significant.

2.1.1.2 Strain measurement on the borehole end

In this method strain is measured by strain gauges bonded directly onto the rock forming the end of the borehole. The most common method of this type is the CSIR Doorstopper strain cell (Leeman 1964c, Leeman 1969b). This method is illustrated in Figure 3. A BX sized borehole is diamond drilled to a depth which is beyond the influence of the excavation from which the hole is drilled. The end of the borehole is then flattened with a special diamond flattening crown, cleaned, and the "doorstopper" cell, which houses a 4 element wire resistance strain gauge rosette, is bonded onto this surface. Initial strain readings are taken, and the cell is then overcored to produce a short length of core stub. Strain readings give the strain relief due to the overcoring, and the corresponding in situ stresses are calculated using elastic theory.



JOB NO
213413

SOLID INCLUSION GAUGE (AFTER BLACKWOOD, 1977)


FIG. NO
2



a) BX BOREHOLE DRILLED TO THE
REQUIRED DEPTH AND END
FLATTENED AND POLISHED WITH
DIAMOND TOOLS



b) STRAIN CELL BONDED ON TO END
OF BOREHOLE AND STRAIN
READINGS RECORDED



c) BOREHOLE EXTENDED WITH BX DIAMOND
CORING CROWN THEREBY STRESS
RELIEVING THE CORE



d) BX CORE, WITH STRAIN CELL ATTACHED,
REMOVED AND STRAIN READINGS TAKEN



JOB N^o
213413

CSIR DOORSTOPPER STRAIN CELL SYSTEM

FIG. N^o
3

CSIR triaxial Strain Cell/CSIRO HI Cell

These two approaches are considered together since they are the same in principle, the differences being in the structure of the cell and in the detail of their practical implementation. The former approach was developed in South Africa (Leeman and Hayes 1966, Leeman 1969b, van Heerden 1976) and the latter in Australia (Worotnicki and Walton 1976).


The preparation for measurements using these methods is very similar to that for the borehole deformation meter, and the steps in making a measurement are summarised in Figure 4. The walls of the pilot hole must be thoroughly cleaned since the strain gauges are bonded to these surfaces. The cells include three wire resistance strain gauge rosettes, consisting of 3 or 4 elements each, which are located at specific angles around the borehole circumference, as illustrated in Figure 4.

Once the gauges are bonded and initial strain readings recorded, the cell is overcored. With the CSIRO cell, strain readings are recorded during the progress of the overcoring. In situ stresses are calculated from the measured strain reliefs using elastic theory. The complete state of stress in the rock is determined by the single measurement.


The method requires the same drilling facilities as the borehole deformation meter. In good rock conditions it is possible to use a smaller diameter overcore such as an NXCU or even an NXC size.

Amongst the many practical factors necessary, successful measurements are dependent on obtaining a sufficient length of intact overcore. It has been found that this is difficult to obtain under high stress conditions when discing of core may occur (Worotnicki 1993) or dog earing may be incipient or present on the walls of the borehole.


It is very unlikely that more than one measurement will be obtained in a single borehole in one mining shift.




STRAIN GAUGES IN THE CSIRO HI CELL




a) BOREHOLE DRILLED TO THE DEPTH AT WHICH THE STRESS IS TO BE DETERMINED





b) EX BOREHOLE DRILLED INTO THE END OF THE BOREHOLE



c) STRAIN CELL GLUED IN THE EX PORTION OF THE BOREHOLE AND STRAIN READINGS TAKEN



d) EX PORTION OF THE BOREHOLE OVERCORED AND STRAIN RELIEF MEASURED



STRAIN GAUGES IN THE CSIR CELL



JOB N^o
213413

CSIR AND CSIRO TRAXIAL STRAIN CELL
SYSTEM OF IN SITU STRESS MEASUREMENT

FIG N^o
4

Bored raise rosette overcoring

This method is essentially the application of the CSIR or CSIRO triaxial cell approach, but on a large scale (Brady et al 1976, Chandler 1993). It requires the presence of a bored raise or tunnel, that is, a circular opening with smooth surfaces, which is effectively a very large diameter borehole.

The rosettes are of long gauge length, which can be 200 to 300 mm, and are located at three angles around the periphery of the circular excavation. In the original application (Brady et al, 1976) the rosettes consisted of sets of pins into the rock, with the distance between the pins being measured using a mechanical gauge. In the more recent application (Chandler, 1993), wire resistance strain gauges with a gauge length of 120 mm were bonded to the rock surface.

The individual rosettes are overcored using a large diameter coring bit and the resulting strain relief measured. In the original application a 360 mm diameter thin walled bit was used for overcoring. To provide additional data, and a check on results, pins can be installed on a larger diameter, outside the overcore diameter. They will then be undercored, but will also reflect the strain relief.

The in situ stress is calculated from the strain relief measurements using elastic theory, and the complete state of stress in the rock is yielded.

The method requires special drilling equipment and the availability of a bored raise, and would be a costly method to apply in the gold mines. It is therefore unsuitable as a routine application method. It has the advantage, however, of taking into account a large volume of rock. Surfaces of the bore can be inspected to select suitable locations for the rosettes, and the effect of local material and structural variation can be avoided.

Interfels Borehole Slotter

In this system, the stress and strain relief is created by cutting a slot in the wall of the borehole (Bock and Foruria 1983, Bock 1986). The strain relief adjacent to this

slot is measured during the slotting process. The method is illustrated in Figure 5.

Measurements from three slots are required to enable the calculation of the secondary principal in situ stresses in a plane normal to the axis of the borehole. To obtain the complete state of stress in the rock, slotter measurements need to be carried out in boreholes drilled in three different orientations.

The method is attractive from a practical point of view in that many slots can be cut during a mining shift, and many slots can be cut in a single borehole. Typically 20 to 30 slots can be cut in hard rock during a shift, which corresponds with the equivalent of about 8 doorstopper measurements. The method requires a diamond core drilled hole with a diameter of between 95 and 103 mm. The holes need to be drilled carefully to ensure that they are straight, since the equipment "pod" inserted into the hole is 1,3 m in length. Holes for measurements may be pre-drilled, and the presence of a coring machine during the measurement process is not necessary. There is no requirement for overcoring. The presence of water is not detrimental to a measurement unless it is of sufficient volume to interfere mechanically, in terms of flow forces, with the equipment and measuring strain gauge.

Since the measurement of strain relief is by means of a mechanical contact strain gauge, the condition of the rock on the wall of the borehole is critical to a good result. Cracking or spalling, which might occur under high stress conditions, will have an adverse effect on the measurement and could invalidate the result. The method can be successful in significantly jointed rocks in which other strain relief methods will probably be unsuccessful.

2.1.2 Borehole inclusion stressmeters

As with the strain instruments dealt with above, borehole stress meters depend on the deformation of the borehole as a result of an overcore to obtain the result. A strain cell is a "soft" instrument which deforms with the rock and offers no effective resistance to this deformation. A stress meter is a "rigid" instrument which provides considerable resistance to the deformation of the borehole. As a result of this





ILLUSTRATION OF SLOTS CUT INTO THE SIDE OF A BOREHOLE



SECTION THROUGH A SLOT, SHOWING THE STRAIN MEASUREMENT DEVICE



JOB NO
213413

INTERFELS BOREHOLE SLOTTING SYSTEM OF
IN SITU STRESS MEASUREMENT

FIG. NO
5

resistance a stress is induced in the instrument which gives a measure of the stress in the rock.



Since borehole stress meter instruments deform differently from the actual rock, they have to be calibrated before use. If the effective modulus of elasticity of the instrument is greater than five times the modulus of the rock, it is not necessary to know the modulus of the rock accurately. The stressmeter can be calibrated in material having a modulus approximately the same as the rock. If the effective modulus is similar to that of the rock, the calibration becomes very sensitive to variations in the rock modulus, and the accuracy of results suffers.

For these reasons it is unlikely that stress meters would be successful in the high modulus quartzites occurring in gold mines. They have not been widely used for in situ absolute stress measurement in rock, but appear to have greater application for the measurement of stress changes.


2.1.3 Hydraulic fracturing method

Hydraulic fracturing, as a method of in situ stress measurement, is relatively new. In his detailed consideration of methods of in situ stress measurement (Leeman 1964b, 1964c, 1964d), and his detailed literature review (Leeman, 1969b), Leeman made no mention of the hydraulic fracturing method. It appears that Fairhurst (1964) was the first to suggest the method for in situ stress measurement, and early research in the field was carried out by Haimson (1968) and Von Schoenfeldt (1970). Hydraulic fracturing is now the best known method for assessing in situ stress at great depth and is in common use (Haimson, 1993). It is the one stress measurement method that gives a direct output of stress without the need for calibration or calculation of stress from measured strain using appropriate stress-strain theory.

In the method, fluid pressure is applied to a test section of a borehole isolated by borehole packers in a series of pressurisation cycles. This is illustrated in the sketches in Figure 6. The pressures which are required to generate, propagate, sustain, and reopen fractures in the test section are related to the in situ stress field.



HYDRAULIC FRACTURING METHOD OF IN SITU STRESS MEASUREMENT



In particular, when the induced fracture is sub-parallel to the borehole axis, the minimum principal stress is equal to the measured shut-in pressure (see Figure 6).

A significant amount of equipment is required to carry out a full scale hydrofracture test, including the following: inspection equipment in the form of a borehole television camera or an impression packer system, which is required to observe the orientation of the induced fracture; a double packer system with sufficient capacity to cater for pressures corresponding with the in situ stresses; a high pressure pumping system and associated rods, tubes and fluid reservoir; measurement equipment including fluid pressure transducers, pressure gauges for the packer inflation, fluid flow meter and chart recorder or equivalent.

Core drilling is preferable, but not essential, particularly if borehole television inspection equipment is available.

Figure 6 illustrates idealised hydraulic fracturing pressure records. Often, results are not distinct, and considerable interpretation and experience is required to determine a representative shut-in pressure (Guo et al 1993a).

To be able to interpret the orientations of the in situ principal stresses, it is necessary that the borehole is drilled in the direction of one of the principal stresses. This is considered to be a disadvantage for application in the gold mines in that the orientations of the principal stresses are not known, and their determination is one of the aims of the in situ stress measurement. However, if the induced fracture is propagated sufficiently to ensure that it is in the plane normal to the minimum stress, then the shut-in pressure should give an accurate measure of the minimum principal stress. The method, in a simplified form, is widely used for this purpose in civil engineering projects involving pressure tunnels and shafts (Vik and Tunbridge 1986, de Witt 1992). In these cases the minimum principal stress, or the ability of the rock mass to contain the water pressure in the tunnel or shaft, is the important factor. A similar simplified test was used by Ortlepp and Bristow (1990) to determine the minimum principal stress in three different mining environments. The simplified test involved grouting a high pressure steel tube into the borehole, the end of the borehole being pressurised by pumping in the fluid through the steel tube.

Only the hydraulic pressure is monitored. The necessary amount of equipment and instrumentation is therefore substantially reduced and the test can be carried out in a percussion hole.

A variation on the standard hydraulic fracturing method is the HTPF method (hydraulic tests on pre-existing fractures) described by Cornet and Valette (1984), Cornet (1986) and Cornet (1993). As the name indicates, tests are carried out on clearly identified individual pre-existing joint planes. The section of borehole containing this plane is packed off and hydraulically pressurised to reopen the joint plane. The pressure at which this occurs is the stress acting normal to that plane. Additional tests are required across different planes of different orientations to provide sufficient data to determine the complete state of stress in the rock. Cornet (1986) indicates that a minimum of 15 tests is necessary for this. This implies that the method would be very time consuming as well as requiring a significant amount of quality drilling. Visual observation of the joint planes, by means of a television camera, is almost essential to determine the orientations of the planes.

2.1.4 Other borehole methods

The literature contains a large number of papers dealing with different types of strain and stress cells, and many of these are referenced in the bibliography to this report. They deal with different geometries of cells, different types of strain gauges, different installation techniques, etc. Many of them are described in theoretical or prototype form, and have never been applied in real in situ stress measurement situations. They may all be considered as variations of the methods which have been described above. The methods described above are those that have been proved in practice and are most widely used. Their advantages, disadvantages, merits and shortcomings are therefore representative of what is currently available in the field of in situ stress measurement using boreholes, and this will form the basis of an assessment of their applicability in the deep level gold mines.

2.2 The flat jack stress measurement technique

This method is one of the oldest methods of stress measurement and was developed


in France (Tincelin 1952, Habib and Marchand 1952). The method involves the cutting of a small slot into the surface of an excavation, with the deformation of the rock adjacent to the slot, as a result of the cutting of the slot, being monitored. The geometry of the method is shown in Figure 7. Two or more pins are inserted into the rock on either side of the slot and are used as the measurement points. After the slot has been cut a small flat jack is grouted into the slot and then pressurised, with the pin separation again being monitored. When the separation is the same as existed before the slot was cut, the magnitude of the pressure represents the in-situ stress magnitude in the excavation wall at that location normal to the plane of the slot.

The method requires special jigs to set up the geometry for mounting the pins and the location of the slot. A special saw is required for cutting the slot. Alternatively it is possible that a series of overlapping holes can be drilled to produce the slot. Grout of similar strength to that of the rock is required. Separations between the pins are measured by means of a removable mechanical or electrical strain gauge.


The method provides a direct measure of the stress acting in the skin of the excavation. Each flat jack yields one component of this stress. To obtain the complete state of stress, at least 6 flat jack tests, but preferably more, must be carried out at different orientations, as shown in Figure 7. This stress field is the disturbed stress field around the excavation. To determine the virgin in situ stress, the stress field around the excavation has to be extrapolated by application of the theory of elasticity or by use of numerical modelling techniques.

It will be clear that, for the method to be applied successfully, the rock quality on the surface of the excavation must be in very good, unfractured and unbroken condition. With regard to the deep level gold mines this is considered to be a major disadvantage, and it is unlikely that flat jack tests will have any chance of success under these conditions.

A variation on the use of flat jacks is the use of curved jacks that can be installed in boreholes (Jaeger and Cook, 1963; Bowling, 1976). These do not appear to have been commonly used.



EXAMPLE OF THE LAYOUT OF SLOTS FOR FLAT JACK TESTS



SECTIONS THROUGH INSTALLED FLAT JACKS



JOB NO
213413

FLAT JACK METHOD OF IN SITU STRESS MEASUREMENT

FIG. NO
7

2.3 Back analysis of in situ stresses from field measurements

Back analysis is a technique which has been developing over the past 20 years, and has been made feasible by the availability of computers and numerical stress analysis techniques. Kavanagh (1973) appears to have been the first to use the technique, and Kirsten (1976b) was the first to apply it in the rock mechanics field for determination of rock mass deformation properties. The principle of the method is that the in situ stresses and the deformation characteristics of the rock mass interact and thus, when an opening is created, the resulting deformation or stress changes can be used to back-calculate the stresses and deformation properties.

The method makes use of the measured response of the rock mass, by means of installed instruments, as a result of an adjacent excavation or step in excavation excavation. For example, this could be produced by the advance of a tunnel, the excavation of a chamber in stages, or the advance of a slope face. The measurements that could be used are displacements, strains or stresses, or a combination of them.

Sakurai and Shimizu (1986) describe a simplified form of in situ stress determination using back analysis. In this approach two assumptions are made - the value of Poisson's ratio is assumed not back calculated, and the vertical stress is calculated from the overburden. The modulus of elasticity and the in situ stresses are then back analysed making use of a boundary element numerical analysis formulation.

Zou and Kaiser (1990), Kaiser et al (1990) and Wiles and Kaiser (1994a, 1994b) deal specifically with the determination of in situ stress from excavation induced changes, using monitored data from installed instruments, mainly strain cells.

It is preferable if the response of the rock is elastic, but non-linear (Sakurai, 1979) and elasto-plastic behaviour (Akutagawa, 1991) can be accommodated in back analysis approaches.

The method requires a situation in which facilities and time exist for the installation of suitable instruments, as well as the facility of careful additional excavation to create the deformation response. The appropriate numerical analysis technique and

computer facilities are also required.

Compared with strain cell overcoring systems, a large volume of rock is involved in this method, particularly if the excavations are of significant size.

2.4 Borehole observational methods

Leeman (1964b) drew attention to the possibility of estimating rock stress from borehole sidewall fracture and from diamond drill-core fractures, and Cloete et al (1972) used the latter to estimate the magnitude of the in situ stress field.

In South Africa borehole sidewall fracture is usually referred to as "dog earing", but in the international literature this phenomenon is described as "borehole breakout". As indicated by Leeman, dog earing is a very useful indicator of level of stress, and the observations can be made in any boreholes that are available. The fact that the dog earing occurs indicates that the stresses are high enough to cause failure of the rock in the stress concentrated zone on the wall of the borehole. In addition, the alignment of the dog ears gives the orientation of the minimum secondary principal stress in the plane normal to the borehole axis.

Zoback et al (1985) and Haimson and Herrick (1986) extend the above thinking to the possibility of relating the dimensions of the breakouts to the principal stress magnitudes. From laboratory investigations the latter authors found that the depth and circumferential extent of the completed breakout were directly proportional to the state of stress normal to the borehole axis. Zoback et al (1986) indicate the possibility of using breakouts for in situ stress estimation when, due to the occurrence of breakouts, the application of hydraulic fracturing is very difficult. They believe that the approach deserves further attention.

At this stage, the use of observations of dog earing for in situ stress estimation remains very qualitative. It nevertheless is a valuable indicator of stress magnitude and, particularly, stress direction. It is naturally of no use in situations where breakouts do not occur.

Discing of borehole core is also an indicator of high stress. It is often the case that, where dog earing is observed in a borehole, discing of the core occurs. However, it is most unlikely that core discing behaviour could be used as a quantitative means of determining in situ stress. Stacey (1982) indicates that discing depends significantly on the properties of the rock and the stress in the direction of the borehole axis. In addition, the type and technique of drilling, including the drill thrust, can affect the occurrence of discing significantly (Kutter, 1991). With regard to determination of principal stress directions, however, Dyke (1989) considers that the shape of discs can provide a good estimate of these directions, even in cases in which the borehole axis is not in one of the principal stress directions.

2.5 Other methods

Many other methods for determination of in situ stresses have been proposed, developed theoretically, developed experimentally, and applied occasionally.

These other methods include the use of geophysical techniques (sonic method, for example, Obert, 1939; Buchheim, 1953; resistivity method in coal, for example, Brown et al, 1958), analysis of micro-cracking in destressed rock samples (Charlez et al 1986b), measurement of anelastic strain recovery (Enever and McKay, 1976; Matsuki and Takeuchi, 1986), a dilatometer instrument or similar to pressurise a borehole (Helal and Schwartzmann, 1983; Charlez et al, 1986a; Ljunggren and Stephansson, 1986), Kaiser effect gauging by monitoring acoustic emissions (Hughson and Crawford, 1986), and borehole deepening (De La Cruz and Goodman, 1970).

It is unlikely that any of these methods will be used commonly, and therefore no significant description of them is given.

3 APPLICABILITY OF EXISTING METHODS OF IN SITU STRESS MEASUREMENT TO DEEP LEVEL GOLD MINES

Many existing methods of in situ stress measurement have been outlined above. It is considered that a limited number have application to the deep level gold mines. Methods that may have application from a technical point of view are as follows:

- borehole overcoring methods, including the CSIR doorstopper strain cell, the CSIR triaxial strain cell, and the CSIRO HI cell
- large diameter overcoring in a bored raise
- hydrofracturing
- back analysis from monitored deformations around excavations.

In the following sections the practical applicability of each of the above four groups in deep level gold mines will be considered.

3.1 Borehole overcoring methods

Borehole overcoring methods rely on the measurement of small changes in strains on the surfaces of the boreholes, or changes in diametral dimensions. The volume of rock involved in each measurement is very small, and the actual measurements made are therefore significantly influenced by the local behaviour of the rock at the measurement location. In fact the measurements can be affected by the grain size in the rock and strain gauges can be of similar size to grains. In addition, the condition of the rock at the measurement location can affect the results considerably. For example, the occurrence of minor micro-cracking beneath a strain gauge or diametral measurement point can affect the magnitude of the strain or deformation reading considerably. This is illustrated very clearly by the results reported by Chandler (1993), which are reproduced in Figure 8. The in situ stress measurements described by Chandler were carried out in massive granite rock, which could be considered to be a "perfect" medium for measurements. In spite of this, microcracking in the granite led to large variations in the apparently good quality results obtained (Martin and Christiansson, 1991). In this good quality rock, variations of more than 50% in measured in situ stresses were obtained in a single hole. Variation in results obtained by different overcoring methods, under laboratory conditions, are presented by Cai et al (1995). These results show a maximum error of about 30%, and a typical error of about 10%, even under the controlled laboratory test conditions.





FIG. N^o
8

VARIATION OF RESULTS FOR OVERCORE METHODS COMPARED WITH BORED RAISE OVERCORING AND BACK ANALYSIS TECHNIQUE

JOB N^o
213413



Under very high stress and less perfect rock conditions, large variations in apparently good measurements can be expected. Under such conditions, it is difficult to determine which are the "correct" values. A possibility is to apply statistical techniques, but this implies that a large number of results will be obtained on which to base the analyses. This has a significant disadvantage since overcoring measurements require a diamond drill, special bits, and associated services (water, compressed air and electricity usually) to be on standby for the duration of the measurement programme. An experienced driller and measurement technician are also required for the duration of the programme. Measurements can typically be carried out at the rate of one per shift for triaxials, and about two for doorstoppers. Time is also required after the site work to carry out laboratory core testing and to calculate and interpret the results. Strain cells, particularly the CSIRO HI cells, are expensive items. In addition to the above, there are many experimental difficulties which can develop, for example, breaking of the core during overcoring; instrumentation problems due to the harsh underground environment; the presence of water in the hole; glue creep and debonding. All of these can result in a failed measurement. It may be concluded that a successful overcoring programme will be expensive.

Overcoring methods measure strain or deformation, and the in situ stress has to be calculated from these values using elastic stress-strain theory. This requires the deformation properties of the rock to be determined, as well as the assumption that the properties determined are representative for each measurement. With the triaxial approaches this can be overcome to a certain extent by testing the actual overcore, with the cell still in place, and monitoring the deformation behaviour at each gauge location.

It may be concluded from the above that, although overcoring methods are theoretically applicable in deep level mines, and have been used under these conditions, they have many disadvantages which make them non-ideal for this purpose. In summary, these disadvantages are their variability, their cost and the experimental reliability.

3.2 Large diameter overcoring in a bored raise

Many raises are excavated by raise boring on the deep level gold mines. There is thus a source of measurement sites for application by this method. The method involves a much larger volume of rock than the borehole overcoring method, and thus overcomes the problem of small scale variability of rock material. This is clear from the results shown in Figure 8. In addition, a considerable amount of redundancy of measurement values can be introduced into the method, and this will allow dubious individual values to be eliminated, and statistical optimisation to be applied.

A disadvantage of the method is that it is dependent on the location of raise bores, and cannot be carried out at a specific location at which in situ stresses are required.

The method requires physical access to the actual measurement location, and, for safety purposes, this may require special support to be installed in the raise. In addition, special large diameter overcoring equipment is required, with the associated services and personnel. Laboratory testing of the overcores, or of cores taken from the overcore, is required. It is clear from the above that, even to obtain one in situ stress measurement result, the method will be very expensive. At best, such a measurement will be inconvenient for a mining operation.

As with the borehole overcore methods, the in situ stresses are calculated from the measured strain reliefs. The results are therefore dependent on the measured rock stress-strain relationships, and on the validity of the elastic solution used for in situ stress calculation.

In conclusion, the method is likely to provide a more reliable stress measurement result than borehole overcoring. However, it is much less flexible, and likely to be very expensive.

3.3 Hydrofracturing

In Section 2.1.3 it was stated that hydraulic fracturing is the best known method for assessing in situ stress at great depth. This statement applies to the determination of crustal stresses in vertical boreholes. If the method has been applied in deep level gold mines, no results have been published.

The method requires special equipment, and associated services and personnel, to carry out a measurement. The borehole must be diamond drilled, or inspected with a television camera if percussion drilled. Since packers are inserted in the borehole to seal off the test sections, the straightness and wall quality of the borehole are important. In boreholes in which spalling is occurring, there may be a risk of not being able to insert (or recover) the packers, and it may also not be possible to seal off the borehole satisfactorily. In vertical boreholes in the oil industry in which hydrofracturing is usually carried out, drilling fluids are usually present which help to maintain the integrity of the borehole. Special techniques such as this may be necessary if the method was to be applied in the gold mines.

After hydrofracturing, the borehole has to be inspected again, using a television camera, or a special impression of its surface taken using an impression packer, to determine the orientation of the induced fracture.

Interpretation of hydrofracture records can require expert input if the shut-in pressure is not distinct. Interpretation of test results is not a straight-forward activity, and the experience of the interpreter has some effect on the in situ stress values ultimately determined. Different interpreters may derive somewhat different results from the same set of field data.

It is clear from the above that the application of the hydrofracture method in deep level gold mines would be expensive, and demanding on services. Perhaps the most severe restriction, however, is the requirement that the borehole be drilled in the direction of one of the principal stresses. In general in the gold mines this is not known and is one of the in situ stress parameters to be determined. The HTPF variation of the hydrofracture method described in Section 2.1.3 above, which does

not have this requirement, is not seen as a practical alternative owing to the number of boreholes required for a full in situ stress measurement.

It may be concluded from the above that the hydrofracture method is not likely to provide a practical method for application in the deep level gold mines. However, the simplified approach described in Section 2.1.3 above is considered to have significant merit for determining the magnitude of the minimum principal stress, since it provides a direct measurement of stress rather than a strain from which the stress is calculated. Such a test could be implemented in percussion boreholes with a very limited requirement for services. Although the test will yield only the magnitude of the minimum principal stress and not its orientation, it will provide an absolute stress magnitude which can be used to "calibrate" the results obtained from other in situ stress measurement methods. For this reason it is considered to be a practical addition to any other method of in situ stress measurement.

3.4 Back analysis from monitored deformations around excavations

The use of a back analysis technique, based on measured deformation or stress changes around an excavation, has the advantage of testing a large volume of rock. The larger the excavation involved the larger the volume of rock that will be affected. The benefits of such an approach compared with other methods of in situ stress measurement have been outlined by Wiles and Kaiser (1994). The result from the use of this technique is compared, in Figure 8, with those of borehole overcoring and large diameter overcoring in a bored raise.

The method involves the instrumentation of an excavation, whose dimensions will be enlarged in some way, such as for example, the face advance of a tunnel, the excavation of a tunnel out of a larger excavation, the slipping of an opening, etc. Instrumentation must be chosen carefully, and the whole programme well planned to obtain the most appropriate deformation and stress data (Akutagawa, 1991). Several stages of excavation may be monitored if applicable, and the data obtained used to make several predictions of the in situ stresses. In this way, with an excess of instrumentation, and several stages of back analysis, the reliability of the method may be evaluated in each particular application.

From a practical point of view, the calculation of in situ stresses requires linearly elastic rock deformation behaviour. This may be restrictive in very high stress environments, but, if required, it should be possible to engineer the enlargement such that the induced deformations being measured are essentially in the elastic regime.

The application of the method is restricted to the availability of sites at which excavation enlargements are being made (unless enlargements are made specifically for the purposes of in situ stress measurement). This will have a large interference factor on mining operations. Sophisticated instrumentation is required, with associated special borehole drilling, and this implies significant cost.

The reliability and survivability of instrumentation in deep level gold mines is known to be a serious problem, particularly if it is required over a significant period of time.

It may be concluded that back analysis as a method of in situ stress determination has significant applicability in the deep level gold mining environment if suitable opportunities arise. However, it is inflexible in that it would not, under normal circumstances, be practical to implement the method only for the specific purpose of in situ stress measurement, since the costs will be high and the interference factor will probably be significant.

3.5 Summary regarding the applicability of existing methods of in situ stress measurement

Of the many methods of in situ stress measurement that are available and have been published in the literature, the majority have been rejected immediately as not being practically applicable in the deep level gold mines. Only a few of the methods have been identified as being possibly applicable, and their advantages and disadvantages have been dealt with in more detail above. In summary, the applicability of these few methods is as follows:

- Borehole overcoring methods: have been and can be used, but suffer from the disadvantages of poor reliability, requirement for services, and high cost per

successful measurement programme. Applicability is considered to be poor.

- Large diameter overcoring: greater reliability, but is inflexible in terms of location, is demanding in terms of services, and hence is costly. Applicability is considered to be poor.
- Hydrofracturing: demanding in terms of services, specialised equipment and expert interpretation, and has a major drawback in that the borehole must be drilled in the direction of one of the in situ principal stresses. Applicability is considered to be very poor. However, applicability of a simplified method, in which only the magnitude of the minimum principal stress is determined, is considered to be significant. This, however, does not on its own satisfy the requirements of the SIMRAC Project.
- Back analysis from monitored deformations around excavations: to implement excavation enlargements, with associated instrumentation, specifically for the purposes of in situ stress measurement is not considered to be practically applicable. Costs will be high and flexibility low. Where appropriate opportunities arise to use the method, ie, when the excavation is going to be enlarged anyway and instrumentation can be installed economically, it is considered that it is applicable. General applicability in the deep level gold mines is considered to be poor.

4 REQUIREMENTS FOR A RELIABLE COST EFFECTIVE TECHNIQUE FOR IN SITU STRESS MEASUREMENT IN DEEP GOLD MINES

None of the existing methods of in situ stress measurement is considered to have practical applicability in deep gold mines. This is for a variety of reasons which have been outlined above. From experience of involvement in numerous in situ stress measurement programmes in mines and tunnels, using a range of the techniques described above, the following are considered to be the requirements for a reliable, cost effective technique for in situ stress measurement in deep gold mines:

- the technique must be undemanding on the requirement for services provided by the mine. It would probably require the provision of compressed air, but should not require water or power. It must have as little impact as possible on the mining production and exploration operations, and should require no

input of time from these personnel. If possible, it should require no attendance by any mine personnel during the measurement programme. Mine personnel should clearly be welcome to participate, should they wish to do so, but there should be no requirement for their involvement. In summary, the technique should, as far as possible, minimise the input required from the mine in terms of personnel and services.

- the technique should be low cost with regard to all aspects - cost of preparation, cost of installation, cost of instrumentation and cost per measurement, and economical in terms of time requirements.
- the technique should allow many measurements to be made in a single mining shift. The preference is for a large number of lower accuracy measurements rather than one or a few apparently high accuracy results. This will allow the results to be treated statistically and therefore avoid localised effects.
- the technique should not be sensitive to high stress effects such as spalling and microcracking of the rock.
- the technique should be flexible. It should be possible to implement at very short notice, require a minimum of preparation, be possible to apply in excavations of limited size, and be non-restrictive in terms of location. It should also be able to be implemented on a stop-start basis, not requiring a long continuous period for a measurement programme, ie it should be able to fit in with the availability of measurement sites, transport, personnel etc.
- the technique should preferably not require the retrieval of rock cores and laboratory testing to determine the deformation properties of the rock or rock mass.


Based on the above requirements, an in situ stress measurement technique which will be practically applicable in the deep gold mines has been developed conceptually, as required in terms of the SIMRAC proposal submitted. The proposed method, and the theoretical feasibility analyses that have been carried out, are given in the following section.

CONCEPTUAL DEVELOPMENT OF A RELIABLE COST EFFECTIVE
TECHNIQUE FOR GROUND STRESS MEASUREMENTS IN DEEP GOLD
MINES


The conceptual method of in situ stress measurement, which has been developed from consideration of existing methods, and from the requirements set out above, is as follows (this should be read in conjunction with the illustrations in Figure 9, and the geometry of the method is illustrated in Figure 10):

- a borehole-based system, using percussion boreholes drilled using a conventional jackhammer
- creating the enlargement, or stress/strain change, not by overcoring, but by drilling parallel, overlapping holes
- control of the direction of adjacent holes, and prevention of sideways movement of drill chips, by means of a special borehole guide
- measurement of deformation changes in the first borehole, as a result of the drilling of the third borehole, by means of a borehole deformation meter
- sequential deformation change measurements down the length of the borehole, alternately moving the deformation meter and advancing the third borehole, thus obtaining numerous individual results in a single borehole set
- measurements carried out in three different borehole orientations at each site to provide sufficient data for the complete state of stress to be determined
- calculation of the in situ stress field by back analysis of monitored deformations using an appropriate numerical stress analysis program. Sufficient data would be obtained to allow the deformation properties to be determined as part of the back analysis procedure
- optimisation of results making use of the redundancy in number of data.

It is considered that the technique defined by this concept will satisfy all the requirements identified in Section 4 above. Specifically, the use of jackhammers to drill percussion holes means that the operation will be quick and low cost. The jackhammer could even be provided by the stress measurement operator, and the mine would then only have to provide compressed air at the measurement site.



JOB N^o
213413



CONCEPTUAL METHOD OF IN SITU STRESS MEASUREMENT
APPLICABLE TO DEEP GOLD MINES

FIG. N^o
9

The use of percussion drilling also means that many measurements can be made in one shift - probably three to four per hour. The implication of this is that more than 20 results could be achieved per day. If the sites are pre-drilled, a sufficient set of measurements could probably be completed in two days.

The use of a reusable deformation meter "pod" rather than disposable cells means that instrumentation costs will be maintained at a low level.

All operations could be carried out by personnel from the measurement operator without any requirement for personnel from the mine.

It should be possible for back analysis predictions to be calculated each day after in situ deformation results have been obtained. This will allow predictions to be updated progressively, decisions to be made on the requirement for further data, and hence for the programme to be completed at the earliest opportunity thus minimising cost.

Previous borehole methods of in situ stress measurement have depended on the availability of a closed form solution for the stress distribution around the borehole. This allowed solutions to be developed for the end of the borehole (for doorstoppers or hemispherically shaped cells), the surface of the borehole (for CSIR and CSIRO triaxial strain cells, and for the borehole slotter), and for diametral deformation changes (for borehole deformation gauges and for solid inclusion cells). The method proposed above has become possible because of the development of the back analysis technique. The application of this technique does not depend on the availability of a standard elastic stress distribution solution, but on the availability of a numerical stress analysis technique, for example a finite element or boundary element method.

5.1 Stress analyses of the concept

Stress analyses of the proposed geometry of the method have been carried out to prove its theoretical feasibility. The following were the aims of the theoretical analyses:

- to prove that deformations induced around the first borehole by the drilling of the third borehole would be of sufficient magnitude to measure easily
- to determine the effect on the deformations of failure around the boreholes due to overstress
- to determine the length over which the third borehole must be drilled to influence completely the measurement location in the first borehole.


Preliminary analyses for the first purpose were carried out using EXAMINE 2D, a simple two-dimensional boundary element stress analysis program. The indications were positive and subsequent analyses for the first and second aspects were carried out using 2D FLAC. Analyses using 3D FLAC were carried out for the third purpose.

The geometry of the models used for analyses, as illustrated in three dimensions in Figure 10, involved three 40 mm diameter boreholes with a 5 mm overlap. The lengths of the boreholes in the three-dimensional model were 600 mm for the first two holes and about 300 mm for the third hole.

For all analyses the following elastic rock properties were used:

Modulus of elasticity:	70 GPa
Poisson's ratio:	0,2

A mining depth of about 3000 m was assumed for the analyses, corresponding with field stresses of 75 MPa vertical and 37,5 MPa horizontal.



JOB Nº
213413

PERSPECTIVE VIEW OF THE PROPOSED METHOD

FIG. Nº
10

5.1.1 Two-dimensional elastic analyses

Analyses were carried out for both a vertical/horizontal as well as an inclined principal in situ stress field. The vertical and horizontal displacement results from the analyses are presented in Figures 11 and 12. It can be seen from these results that the net closure across the diameter of the first borehole as a result of the drilling of the third borehole is of the order of 0,14 mm. This order of magnitude can easily be measured with the required accuracy for back analysis purposes.

Under an inclined stress field a non-uniform displacement field results as shown in Figures 13 and 14. Again the magnitudes are sufficient to enable the deformations to be determined satisfactorily.

5.1.2 Two-dimensional analyses allowing rock failure to develop

The above analyses were repeated with rock failure being allowed to develop. Strain softening rock behaviour was assumed, and the properties adopted were as used by Raffield et al (1993).

The results of these analyses are shown in Figures 15 and 16. As a result of rock yield and failure the net displacement across the first borehole increases, but the increase is less than 5%. This is less than the likely measured variations in deformation owing to local variations in rock behaviour and experimental factors.

The implication of the above is that the method is not sensitive to the occurrence of rock failure due to overstress in high field stress conditions. This meets one of the requirements set out above for the proposed method. The extent of rock failure can also be restricted by appropriate choices of orientations of the borehole sets, ie so that their axes are not normal to the probable orientation of the maximum principal stress.

FLAC (Version 3.22)

LEGEND

4/05/1995 10:05
step 8067
3.972E-01 <x< 6.379E-01
6.129E-01 <y< 8.536E-01

Boundary plot





Y-displacement contours

Contour interval= 5.00E-06

O: -2.000E-05

W: 2.000E-05

Steffen, Robertson & Kirsten
Box 55291, Northlands 2116, RS



JOB NO
213413

VERTICAL DISPLACEMENTS AS A RESULT OF THE DRILLING OF THE THIRD HOLE

FIG NO
II

JOB TITLE : ELASTIC MEDIUM

FLAC (Version 3.22)

LEGEND

6/19/1995 11:47
 step 8067
 4.447E-01 <x< 5.727E-01
 6.760E-01 <y< 8.040E-01

Boundary plot



0 2E -2

X-displacement contours

Contour interval= 2.00E-06

D: -6.000E-06

H: 2.000E-06


Steffen, Robertson & Kirsten
 Box 55291, Northlands 2116, RS



JOB N^o
 213413

HORIZONTAL DISPLACEMENTS AS A RESULT OF THE DRILLING OF THE THIRD HOLE

FIG. N^o
 12



FLAC (Version 3.22)

LEGEND

4/11/1995 08:17
 step 7645
 1.416E-01 <x< 9.174E-01
 3.508E-01 <y< 1.127E+00

Boundary plot



0 2E -1


Y-displacement contours

Contour interval= 5.00E-06

L: -1.000E-05

R: 2.000E-05

Steffen, Robertson & Kirsten
 Box 55291, Northlands 2116, FS



JOB Nº
 213413


VERTICAL DISPLACEMENTS AS A RESULT OF THE DRILLING OF THE THIRD HOLE :
 INCLINED STRESS FIELD

FLAC (Version 3.22)

LEGEND

4/11/1995 08:18
 step 7645
 1.416E-01 <x< 9.174E-01
 3.508E-01 <y< 1.127E+00


Boundary plot



X-displacement contours

Contour interval= 2.00E-06
 E: -1.000E-05
 N: 8.000E-06

Steffen, Robertson & Kirsten
 Box 55291, Northlands 2116, PS



JOB Nº
 213413

HORIZONTAL DISPLACEMENTS AS A RESULT OF THE DRILLING OF THE THIRD HOLE :
 INCLINED STRESS FIELD

FIG Nº
 14

FLAC (Version 3.22)

LEGEND



6/19/1995 15:49
step 7003
3.982E-01 <x< 6.309E-01
6.237E-01 <y< 8.563E-01

Boundary plot



Y-displacement contours
Contour interval= 3.00E-06
Z: -1.800E-05

Steffen, Robertson & Kirsten
Box 55291, Northlands 2116, PS



JOB N^o
213413

VERTICAL DISPLACEMENTS AS A RESULT OF THE DRILLING OF THE THIRD HOLE:
STRAIN SOFTENING MODEL

FIG. N^o
15

FLAC (Version 3.22)

LEGEND


6/19/1995 15:51
 step 7003
 3.982E-01 <x< 6.309E-01
 6.237E-01 <y< 8.563E-01

Boundary plot



X-displacement contours
 Contour interval= 2.00E-06
 D: -8.000E-06
 I: 2.000E-06

Steffen, Robertson & Kirsten
 Box 55291, Northlands 2116, RS



JOB N°
 213413

HORIZONTAL DISPLACEMENTS AS A RESULT OF THE DRILLING OF THE THIRD HOLE :
 STRAIN SOFTENING MODEL

FIG. N°
 16

5.1.3 Three-dimensional stress analyses

The purpose of the three-dimensional analyses was to determine the extent of the influence in the first borehole of the face of the third borehole. This is effectively the length of each measurement, which determines the number of measurements that can be carried out in a single hole.

The vertical displacements in a vertical plane along the axis of the first borehole are shown in Figure 17. These results show that, per measurement, the minimum length of percussion drilling required in the third borehole is about 200 mm. The implication of this is that about five measurements can be made per metre length of borehole beyond the influence of the tunnel (excavation) from which the boreholes are drilled. In practice, deformations will be monitored during the drilling process and will indicate clearly when the influence is complete. This could be slightly more or less than the theoretical value determined above.

The requirement for a large number of measurements in a single shift is therefore met on the basis of the theoretical analyses.

6 CONCLUSIONS AND RECOMMENDATIONS

A method of in situ stress measurement, based on the percussion drilling of a set of three overlapping boreholes, and back analysing the in situ stresses from the measured deformations in the boreholes, has been developed in concept. By its very nature, being based on low cost drilling and deformation measuring operations, whose application is very flexible, the method will be cost effective. In concept, the method overcomes the disadvantages of most of the available methods of in situ stress measurement, and therefore should be reliable. It is also aimed at being specifically applicable under the conditions which occur in deep mines, and its feasibility has been proved theoretically.

FLAC3D 1.00


















Step 10698 Perspective
 12:07:52 Thu Jun 15 1995

Rotation: Normal:
 X: 0.00 X: -1.00
 Y: 0.00 Y: -0.00
 Z: 90.00 Z: 0.00


Center: Origin:
 X: -1.526e-05 X: -3.500e+01
 Y: 2.624e+02 Y: 0.000e+00
 Z: -7.221e+01 Z: 0.000e+00

Eye Dist: 2.963e+03
 Size: < 3.611e+02, 4.045e+02 >
 Increment: 10


Contour of Z-Displacement

On Plane	Value
	-1.1070e-01 to -1.1000e-01
	-1.0000e-01 to -9.9000e-02
	-8.9000e-02 to -8.8000e-02
	-7.8000e-02 to -7.7000e-02
	-6.7000e-02 to -6.6000e-02
	-5.6000e-02 to -5.5000e-02
	-4.5000e-02 to -4.4000e-02
	-3.4000e-02 to -3.3000e-02
	-2.3000e-02 to -2.2000e-02
	-1.2000e-02 to -1.1000e-02
	-1.0000e-03 to 0.0000e+00
	1.0000e-02 to 1.1000e-02
	2.1000e-02 to 2.2000e-02
	3.2000e-02 to 3.3000e-02
	4.3000e-02 to 4.4000e-02
	5.4000e-02 to 5.5000e-02
	6.2000e-02 to 6.2811e-02

Steffen, Robertson & Kirsten



FACE OF THE THIRD BOREHOLE →



JOB NO
 213413

VERTICAL DISPLACEMENTS IN A VERTICAL PLANE ALONG THE AXIS OF THE FIRST BOREHOLE, AS A RESULT OF THE DRILLING OF THE THIRD BOREHOLE

FIG. NO
 17

It was stated in the SIMRAC proposal document, which is contained in Appendix A, that the primary output of the research project would be at feasibility level, and that further development would be required for the technique to be developed for routine use. It is recommended that this development should now proceed. From a physical point of view there are several aspects which can be identified at this stage as needing development to ensure that the method can be applied practically. These are:

- the development of a suitable drilling guide which can cope with variation in the straightness of the holes, some variation in the diameter of the holes, and "wedging" due to some closure of the holes, to the impact of the drill and to the packing of the drill chippings. This is considered to be the most significant physical challenge.
- development of a suitable deformation meter. This could be based on deformation meters which are currently in use and have proved their practical capabilities.
- development of the standard back analysis procedure. Back analysis has been developed for numerous applications, and is in reasonably common use internationally. The approach, and an appropriate simple stress analysis program, need to be adapted for the specific in situ stress measurement application.

7 REFERENCES AND BIBLIOGRAPHY

Amadei, B., Goodman, R.E., 1982, The Influence of Rock Anisotropy on Stress Measurements by Overcoring Techniques, *Rock Mechanics* Vol. 15, pp 167-180.

Amadei, B. 1983. Discussion: Stress-strain relations applicable to overcoring techniques in transversely isotropic rocks by van Heerden, W.L., *Int. J. Rock Mech. Min. Sci & Geomech. Abstr.* 20, pp 277-282.

Amadei, B, 1984, In Situ Stress Measurements in Anisotropic Rock, *Int. J. Rock Mech. Sci & Abst.* Vol. 21. No. 6 pp. 327-338.

Amadei, B., Swolfs, H.S., Savage, W.Z., 1988, Gravity-induced Stresses in Stratified Rock Masses, *Rock Mechanics and Rock Engineering* Vol. 21, 1-20.

Anon., *Field Manual for CSIRO Hollow Inclusion Gauge*, pp 1-23.

Akutagawa, S., 1991, *A Back Analysis Program System for Geomechanics Applications*, Doctoral Thesis submitted to University of Queensland 325p.

Aytmatov, I.T., 1986, On Virgin Stress State of a rock mass in mobile folded areas, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 55-59.

Bamford, W.E., 1976, Evolution of Stresses in Rock Masses, as Related to Compressive Strengths and Plate Tectonics, *Investigation of Stress in Rock*, International Society of Rock Mechanics Symposium, Sydney Australia, pp 63-70.

Batchelor, A.S., Pine, R.J., 1986, The results of in situ determination by seven methods to depths of 2500 m in the Carnmenellis granite, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 467-478.

Baumann, H., Becker, A., 1986, Lokale variation regionaler Spannungsfelder an zwei beispielen aus SW-Deutschland und der Schweiz, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 45-53.

Barla, B., Bertacchi, P., Zaninetti, A., Rossi, P.P., Vielmo, I., 1986, Hydraulic fracturing testing method for rock stress measurements in Italy, *Proc. Int. Symp. Rock Stress and Rock Stess Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 331-340.

Becker, R.M, Hooker, V.E. 1967, Some anisotropic considerations in rock stress determinations, U.S. Bureau of Mines, RI 6965.

Bergh-Christensen, J., 1986, Rock stress measurements for the Design of a 965 metre head unlined pressure shaft, Proc. Inst. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 583-590.

Berry, D.S., 1968, The Theory of Stress Determination by means of Stress Relief Techniques in a Transversely Isotropic Medium, Technical Report No 5-68, October 1968, pp 1-36.

Berry, D.S., 1970, The Theory of Determination of stress changes in a Transversely isotropic medium, using an Instrumented Cylindrical Inclusion, Technical Report MRD-1-70, pp 1-36.

Bjarnason, B., Stephansson, O., Torikka, A., Bergstrom, K., 1986, Four years of hydrofracturing rock stress measurements in Sweden, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 421-428.

Blackwood, R.L., 1977, An Instrument to measure the complete stress field in soft rock or coal in a single operation, Proc. Int. Symp. on Field Measurements in Rock Mechanics, Zurich, Vol. 1, pp 137-150.

Blackwood, R.L., Buckingham, C., 1986, A remotely operated borehole deformation gauge for monitoring stress change in rock, Proc, Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 369-374.

Blackwood, R.L., Hargraves, A.J., McKay, J., 1976, Absolute Stress Investigations in Coal at Appin Colliery, New South Wales, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 17-22.

Blackwood, R.L., Sandstrom, S., Leijon, B.A., 1986, A study of the bond strength in cemented epoxy solid inclusion stress cell installation, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 523-530.

Bock, H., Borehole Slotter System JCU/IFB 096, Interfels GmbH.

Bock, H. and Foruria, V., 1983, A Recoverable borehole Slotting Instrument for In Situ Stress Measurements in Rocks Not Requiring Overcoring, Int. Symp. on Field Measurements in Geomechanics Zurich, September 5-8, 1983, pp 15-29.

Bock, H., 1986, In-situ validation of the bore-hole slotting stressmeter, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 261-270.

Bois, A.P., Ballivy, G., Saleh, K., 1994. Monitoring Stress Changes in Three Dimensions Using a Solid Cylindrical Cell, Int. J. Rock Mech. Min. Sci. & Geomech. Abstr Vol. 31. No 6, pp 707-718.

Bonnechère, F.J., Cornet, F.H., 1977, In situ stress measurements with a borehole deformation cell, Proc. Int. Symp. on Field Measurements in Rock Mechanics, Zurich, Vol. 1 pp 151-159.

Boone T.J., Ingraffea A.R., Roegiers J.C., 1991, Simulation of Hydraulic Fracture Propagation in Poroelastic Rock with Application to Stress Measurement Techniques, Int. J. Rock Mech Min. Sci & Geomech. Abstr. Vol 28, No 1, pp 1-14.

Bowling, A.J., 1976, Surface Rock Stress Measurement with a New Cylindrical Jack, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 7-11.

Brady, B.H.B., Friday, R.G., Alexander, L.G., 1976, Stress Measurement in a Bored Raise at the Mount Isa Mine, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 12-16.

Brady, B.H.G., Lemos, J.V., Cundall, P.A., 1986, Stress measurement schemes for jointed and fractured rock, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 167-176.

Bredehoeft, J.D., Wolff, R.G., Keys, W.S., Shutter, E. 1976, Hydraulic fracturing to determine the regional in situ stress field in the Piceance Basin, Colorado, Geol. Soc. Am. Bull., Vol 87, pp 250-258.

Bridges, M.C., Gladwin, M.T., Greenwood-Smith, R., Muirhead, K., 1976, Monitoring of Stress, Strain and Displacement in and Around a Vertical Pillar at Mount Isa Mine, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 44-49.

Brown, A., Cochrane, T.S., Patching, T.H. 1958, Ground stress studies in coal mines of Western Canada - A progress report, Can. Min. Metall. Bull., November 1958.

Brown, S.M., Leijon, B.A., Hustrulid, W.A., 1986, Stress distribution within a artificially loaded jointed block, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 429-440.

Buchheim, W. 1953, The problem of determining rock pressure by acoustic means, Bergakademie, Vol 1.

Cahnbley, H.K.R., 1976. A Critical Assessment of Stress Measurements in Sedimentary Rock, Proceeding of the Symposium on Exploration for Rock Engineering, Johannesburg, November 1976, pp 67-73.

Cahnbley, H.K.R. 1965, Discussion of papers by Leeman (1964b, 1964c, 1964d), JI S. Afr.Inst. Min. Metall., Vol 65, pp 408-423.

Cai M, Blackwood R.L., 1991, A Technique for the recovery and Re-use of CSIRO Hollow Inclusion Cells, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 28, No 2/3, pp 225-229.

Cai, M, Qiao, L. and Yu, J, 1992, Techniques for Increasing In-situ Stress Measurement Accuracy, Proc. Western Australian Conf. on Mining, Geomechanics, Kalgoorlie, 1992, pp 311-317.

Cai, M, Qiao, L. and Yu, J, 1995, Study and Tests of Techniques for Increasing Overcoring Stress Measurement Accuracy, Int. J. Rock Mech. Min. Sci. & Geomech. Abstr. Vol 32, No 4, pp 375-384.

Carlsson, A., Christiansson, R., 1986, Rock stresses and geological structures in the Forsmark area, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 457-465.

Chandler, N.A., 1993, Bored Raise Overcoring for *In Situ* stress Determination at the Underground Research Laboratory, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 30, No 7, pp 989-992.

Charlez, Ph., Saleh, K., Despax, D., Julien, Ph., 1986a, A new way to determine the state of stress and the elastic characteristics of rock massic, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 313-322.

Charlez, Ph., Hamamdjian, C., Despax, D., 1986b, Is the microcracking of a rock a memory of its initial state of stress?, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 341-350.

Chambon, C., Revalor, R., 1986, Statistic analysis applied to rock stress measurements, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 397-410.

Cloete, D.R., Collett, P.A.G., Cook, N.G.W., Jager, A.J., White, A.J.A. 1972, The nature of the fracture zone in gold mines as revealed by diamond core drilling, Ass. Mine Managers of S. Afr. Papers and Discussions, 1972-73, pp 107-122.

Coetzer, S.J., Spencer, D. and De Maar, W., 1993, Rock Stress and Mining: A Case History, Proc Symp. S.Afr. National Group of ISRM, Rustenburg, 1993, pp 28-37.

Cooling, C.M., Hudson, J.A., 1986, The importance of in situ rock stress in repository design, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 647-656.

Cooling C.M., Hudson J.A., Tunbridge L.W., 1988, *In Situ* Rock Stresses and Their Measurement in the UK - Part II. Site Experiments and Stress Field Interpretation, Int. J. Rock Mech Min. Sci & Geomech. Abstr. Vol 25, No 6, pp 371-382.

Cornet, F.H., 1993, Stresses in Rock and Rock Masses, Chapter 12 in Comprehensive Rock Engineering, Vol. 3, ed J.A.Hudson, Pergamon Press, pp 297-327.

Cornet, F.H., 1993, The HTPF and the Integrated Stress Determination Method, Chapter 15 in Comprehensive Rock Engineering, Vol. 3, ed J.A.Hudson, Pergamon Press, pp 413-432.

Cornet, F.H., Valette, B., 1984, In Situ Stress Determination from Hydraulic Injection Test Data, Journal of Geophysical Research Vol. 89, No. B13, pp 11.527-11.537.

Cornet, F.H., 1986, Stress determination from hydraulic tests on preexisting fractures - the H.T.P.F. method, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 301-312.

Corthesy R, Gill D.E., 1990, A novel Approach to Stress Measurements in Rocksalt, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 27, No 2, pp 95-107.

Corthesy, R., Leite, M.H., He, G., Gill, D.E., 1994, The RPR Method for the Doorstopper Technique: Four or Six stress Components from One or Two Boreholes, Int. J. Rock. Mech. Min. Sci & Geomech. Abstr. Vol.31, No 5, pp 507-516.

Crouch, S.L., Fairhurst, C. 1967, A four component borehole deformation gauge for the determination of in situ stresses in rock masses, *Int. J. Rock Mech. Min. Sci.*, Vol 4, pp 209-217.

Cuisiat, F.D., Haimson, B.C., 1992, Scale Effects in Rock Mass Stress Measurements, *Int. J. Rock Mech. Min. Sci & Geomech. Abstr.* Vol 29, No 2, pp 99-117.

Cyrul, T., 1983, Notes on stress Determination in Heterogeneous Rocks, *Int. Symp. on Field Measurements in Geomechanics Zurich*, September 5-8, 1983, pp 56-70.

De La Cruz, Rodolfo V. and Goodman Richard E., 1970, Theoretical Basis of the Borehole Deepening Method of Absolute Stress Measurement, *Proc U.S. 11th Symposium on Rock Mech. Rock Mechanics - Theory and Practice*, pp 353-377.

Denkhaus, H.G., 1970, Workshop Manual for the CSIR Triaxial Rock Stress Measuring Equipment, National Mechanical Engineering Research Institute, S. Afr. Council for Scientific and Industrial Research, April 1970.

Denkhaus, H.G., 1973, Instruction Manual for the use of the CSIR Triaxial rock stress measuring equipment, National Mechanical Engineering Research Institute, S. Afr. Council for Scientific and Industrial Research, June 1973.

Detournay, E., Jeffrey, R.G., 1986, Stress conditions for initiation of secondary fractures from a fractured borehole, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 281-288.

de Witt, M.J. 1992, Limits of watertight linings for the delivery tunnel, Lesotho Highlands Water Project, *Proc. TUNCON '92: Design and Construction of Tunnels*, Maseru, Lesotho, S. Afr. National Council on Tunnelling, pp 127-134.

Dey, T.N., Brown, D.W., 1986, Stress measurements in a deep granite rock mass using hydraulic fracturing and differential strain curve analysis, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 351-358.

Doe, T.W., Ingevald, K., Strindell, L., Leijon, B., Hustrulid, W., Majer, E., Carlson, H. 1983, In situ stress measurements at the Stripa Mine, Sweden, Technical Information Report No 44, Lawrence Berkeley Laboratory, University of California, Berkeley.

Du, Y., Aydin, A., 1992, Technical Note The Role of Compression-induced Tension in the Propagation of Hydrofractures: Implications for *In Situ* Stress Measurements at Shallow Depths, Int. J. Rock Mech. Min. Sci. & Geomech. Abstr., pp 589-593.

Dugan, K.J., Hulls, I.H., Miller, D.R. 1993. Recent Experiences with the Borehole Slotter for Measuring In-situ Stress, Geotechnical Instrumentation and Monitoring in Open Pit and Underground Mining, Balkema, Rotterdam, pp 117-124.

Duncan Fama, M.E. and Pender, M.J., 1980, Analysis of the Hollow Inclusion Technique for Measuring In Situ Rock Stress, Int. J Rock Mech. Min. Sci. & Geomech. Abstr. Vol. 17, pp 137-146.

Duvall, W.I., Aggson, J.R. 1980, Least squares calculation of horizontal stresses from more than three diametral deformations in vertical boreholes, U.S. Bureau of Mines, RI 8414.

Dyke, C.G., 1989, Core Discing: Its Potential as an indicator of principal in situ stress directions, Rock at Great Depth, Maury & Fourmaintraux, A.A. Balkema, pp 1057-1064.

Enever, J., Khorshid, M.S.E.D., 1976, A note on the Use of the Hydraulic Fracturing Technique for Estimating In-situ Stresses in Hard and Soft Earthern Materials, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 31-36.

Enever, J., McKay, J., 1976, A note on the Relationship between Anelastic Strain Recovery and Virgin Rock Stresses- A possible Method of Stress Measurement, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 37-40.

Enever, J.R., Chopra, P.N., 1986, Experience with hydraulic fracture stress measurements in granite, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 411-420.

Enever, J.R., Cornet, F., Roegiers, J.C. 1992. International Society for Rock Mechanics Commission of Interpretation of Hydraulic Fracture Records, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol. 29, No 1, pp 69-72.

Eriksson, L.G., Michalski, A., 1986, Hydrostatic conditions in salt domes - a reality or a modelling simplification, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1- 3 September 1986, Centek Publishers, pp 121-132.

Fairhurst, C. 1964, Measurement of in situ rock stresses, with particular reference to hydraulic fracturing, Felsmech. Ingenieurgeol., Vol 3-4, pp 129-147.

Fairhurst, C., 1986, In-situ stress determination - an appraisal of its significance in rock mechanics, Proc. Int. Symp. Rock stress and Rock stress measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 3-17.

Falmagne, V., 1991, Rock Mechanics and Microseismic Monitoring at Ansil, CIM Bulletin - December 1991, Vol. 84, No. 955, pp 46-50.

Fangquan, L., 1986, In situ Measurements, stress state in the upper crust and their application to rock engineering, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 69-76.

Filcek, H, Cyrul, T, 1977, Rigid Inclusion with High Sensitivity, Proc. Int. Symp. on Field Measurements in Rock Mechanics, Zurich, Vol. 1, pp 219-232.

Fitzgerald, D.J., Askew, J.E., Tillman, N.H.B.C., 1976, Stress Measurement for the Design of Underground Mine Openings, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 83-91.

Froidevaux, C., Paquin, C., Angelidis, C., Tzitziras, A., 1980, In Situ Stress Measurements in Greece, *Rock Mechanics*, Suppl. 9, pp 19-20.

Gale, W.J., 1986, The application of stress measurements to the optimisation of coal mine roadway driveage in the Illawarra coal measures, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 551-560.

Gay, N.C., 1975, In-situ Stress Measurements in Southern Africa, *Tectonophysics*, Vol 29, pp 447-459.

Gioda, G. and Sakurai, S., 1987, Back Analysis Procedures for the Interpretation of Field Measurements in Geomechanics, *Int. J. for Numerical and Analytical Methods in Geomechanics*, Vol. 11, pp 555-583.

Gray, W.M., Barron, K., 1969, Stress Determination from Strain Relief Measurements on the ends of Boreholes; planning, Data evaluation and error assessment, Proc. Int. Symp. on the Determination of Stresses in Rock Masses, Lisbon, Paper No. 5, pp 1-10.

Gray, W.M., Toews, N.A. 1974, Optimization of the design and use of the CSIR triaxial strain cell for stress determination, field testing and instrumentation of rock, ASTM STP 554, Am. Soc. Testing Mats, Philadelphia, pp 116-134.

Greiner, G., Lohr, J. 1980. Tectonic Stresses in the Northern Foreland of the Alpine System Measurements and Interpretation, *Rock Mechanics*, Suppl. 9, 1980, pp 5-15.

Gronseth, J.M. 1982, Determination of the instantaneous shut in pressure from hydraulic fracturing data and its reliability as a measure of the minimum principal stress, Proc. 23rd U.S. Symp. on Rock Mechanics, Berkeley, pp 183-189.

Grossman, N.F., Camara, R.J.C., 1986, About the rock stress measurement using the LFJ (Large Flat Jack) technique, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 375-386.

Gross, U., Minkley, W., Penzel, M., 1986, Ergebnisse zur Untersuchung von Gebirgsspannungszuständen und ihre Anwendung für die Hohlraum - und Ausbaudimensionierung, Proc. Inst. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 531-536.

Guangyu, L., Shiwei, B., Jiguang, L., 1986, Twenty years of experience of in-situ stress measurements in China, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 79-89.

Guo, F., Morgenstern, N.R., Scott, J.D., 1993a, Interpretation of Hydraulic Fracturing Pressure: A Comparison of Eight Methods used to Identify shut-in pressure, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 30, No 6, pp 627-631.

Guo, F., Morgenstern, N.R., Scott, J.D., 1993b, An Experimental Investigation into Hydraulic Fracture Propagation- Part I. Experimental Facilities, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 30, No 3, pp 177-188.

Guo, F., Morgenstern, N.R., Scott, J.D., 1993c, An Experimental Investigation into Hydraulic Fracture Propagation - Part II. Single Well Tests, Int. J. Rock Mech. Min. Sci & Geomech Abstr. Vol 30, No 3, pp 189-202.

Habib, P., Marchand, R. 1952, Mesures des pressions de terrains par l'essai de verin plat, Anns Inst. Tech. Batim., Vol 58.

Haimson, B.C. 1968, Hydraulic fracturing in porous and non-porous rock and its potential for determining in-situ stress at great depth, PhD Thesis, University of Minnesota, Minneapolis.

Haimson, B.C. 1974, A simple method for estimating in situ stresses at great depth, ASTM Special Technical Publications 554, Philadelphia, pp 156-182.

Haimson, B.C., 1976, The Hydrofracturing Stress Measuring Technique - Method and Recent Fields Results in the US., Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 23-30.

Haimson, B.C., 1977, Stress Measurements using the Hydrofracturing Technique, Proc. Int. Symp. on Field Measurements in Rock Mechanics, Zurich, 1977, A.A. Balkema, Vol. 1, pp 233-246.

Haimson, B.C., 1978, The Hydrofracturing Stress Measuring Method and Recent Field Results, Int. J. Rock Mech. Min. Sci. & Geomech. Abstr. Vol 15, pp 167-178.

Haimson, B.C., 1980, Near-Surface and Deep Hydrofracturing Stress Measurements in the Waterloo Quartzite, Int. J. Rock Mech. Min Sci & Geomech. Abstr. Vol. 17, pp. 81-88.

Haimson, B.C., 1983, The State of Stress at the Nevada Test Site : A Demonstration of the Reliability of Hydrofracturing and Overcoring Techniques, Int. Symp. on Field Measurements in Geomechanics Zurich, September 5-8, 1983, pp 115-126.

Haimson, B.C., 1993, The Hydraulic Fracturing Method of Stress Measurement: Theory and Practice, Chapter 14 in Comprehensive Rock Engineering, Vol. 3, ed J.A.Hudson, Pergamon Press, pp 395-412.

Haimson, B.C., Fairhurst, C. 1967, Initiation and extension of hydraulic fracture in rock, Soc. Petrol. Engrs J., Vol 7, pp 310-318.

Haimson, B.C., Fairhurst, C. 1970, In situ stress determination at great depth by

means of hydraulic fracturing, Proc. 11th U.S. Symp. Rock Mech., Berkeley, AIME, New York, pp 559-584.

Haimson, B.C., Herrick, C.G., 1986., Borehole breakouts - a new tool for estimating in situ stress?, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 271-280.

Haimson, B.C., Lee, C.F., Huang, J.H.S., 1986, High horizontal stresses at Niagara Falls, their measurement, and the design of a new hydroelectric plant, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 615-624.

Haimson, B., Lee, M., Chandler, N., Martin, D., 1993, Estimating the State of Stress for subhorizontal Hydraulic Fractures at the Underground Research Laboratory, Manitoba, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 30, No 7, pp 959-964.

Hallbjorn, L., 1986, Rock Stress Measurements performed by Swedish State Power Board, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 197-207.

Hanssen, T.H., Myrvang, A., 1986, Rock Stresses and rock stress effects in the Kobbelv area, Northern Norway, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 625-634.

Hast, N., 1980, In Situ Measurements: Stress Fields, Fracture Systems and the Mechanism for Movements in the Gneiss-Granite Area of the Mont Blanc Massif, Rock Mechanics, Suppl. 9, pp 1-3.

Hayes, D.J., 1965, The in situ Determination of the complete state of stress in rock; the principles of a proposed technique, National Mechanical Engineering Research Institute, November 1965, pp 1-17.

Hawkes, I. and Moxon, S., 1965, The Measurement of In Situ Rock Stress Using the Photoelastic Biaxial Gauge with the Core-relief Technique, *Int. J. Rock Mech. Min. Sci.* Vol. 2, pp 405-419.

Helal, H. and Schwartzmann, R., 1983, In Situ Stress measurements with the Cerchar Dilatometric Cell, *International Symposium on Field Measurements in Geomechanics Zurich*, September 5-8, 1983, pp 127-136.

Herget, G., 1973, First Experience with the CSIR Triaxial strain cell for stress Determinations, *Int. J. Rock Mech. Min. Sci & Geomech. Abstr.* Vol 10, pp 509-522.

Herget, G., 1986, Changes of ground stresses with depth in the Canadian shield, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm*, 1 - 3 September 1986, Centek Publishers, pp 61-68.

Heusermann, S. and Pahl, A., 1983, Stress Measurements in Underground Openings by the Overcoring Method and by the Flatjack Method with Compensation, *International Symposium on Field Measurements in Geomechanics Zurich*, September 5 - 8, 1983, pp 1033-1045.

Hooker, V.E., Aggson, J.R., Bickel, D.L. 1974, Improvements in the three-component borehole deformation gage and overcoring technique, U.S. Bureau of Mines, RI 7894.

Hoskins, E.R., 1968, Strain rosette relief measurements in hemispherically ended boreholes, *Int. J. Rock Mech. Min. Sci.*, Vol 5, no. 6, pp 465-474.

Hughson, D.R., Crawford, A.M., 1986, Kaiser effect gauging: A new method for determining the pre-existing in-situ stress from an extracted core by acoustic emissions *Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm*, 1 - 3 September 1986, Centek Publishers, pp 359-368.

Huls, W., Menzel, W., Weber, D., 1986, Spannungssondierungen in Salzpfählern und ihre numerische Modellierung, Proc. Inst. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 537-542.

Hyett, A.J., Dyke, C.G., Hudson, J.A., 1986, A critical examination of basic concepts associated with the existence and measurement of in situ stress, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 387-396.

Ikeda, R., 1993, *In Situ* Stress Heterogeneity and Crack Density Distribution, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 30, No 7, pp 1013-1018.

Ishijima, Y., Goto, T., Kinoshita, S., Isobe, T., Oda, N., 1976, Monitoring of Stress Relief Boring in Akabira Coal Mine, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 100-106.

Isobe, T., Mori, N., Fukushima, A., 1976, Further investigation on the Problems of Underground Rock Destruction by Using Seismic Method, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 50-54.

Jaeger, J.C., Cook, N.G.W. 1963, Theory and application of curved jacks for measurement of stresses, Proc. Int. Conf. State of Stress in the Earth's Crust, Santa Monica, California.

Jupe, A.J., 1994. Confidence Intervals for In Situ Stress Measurements, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol. 31, No 6, pp 743-747.

Kaiser, P.K., Zou, D. and Lang, P.A., 1990, Stress Determination by Back-Analysis of Excavation-Induced Stress Changes - a Case Study, Rock Mechanics and Rock Engineering, Vol 23, pp 185-200.

Kaiser, P.K., Korpach, D., 1986, Stress changes near the face of underground excavations, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 635-646.

Kanduth, H.H., Corthesy, R. and Gill, D.E., 1991, Validation of Borehole Slotting as a Method for in In-Situ Stress Measurements, Proc. 7th Int. Cong. Int. Soc. Rock. Mech., Aachen, Vol. 1, A.A. Balkema, pp 527-532.

Kanagawa, T., Hibino, S., Ishida, T., Hayashi, M., Kitahara, Y., 1986., *In Situ* Stress Measurements in the Japanese Islands, Over-coring Results from a Multi-element Gauge Used at 23 sites, Int. J. Rock. Mech. Min. Sci & Geomech. Abstr. Vol 23, No1, pp 29-39.

Karfakis, M.G., 1986, Hydraulic fracturing stress measurements in anisotropic rocks: a theoretical analysis, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 157-166.

Kavanagh, K. 1973, Experiment versus analysis: Computational techniques for the description of static material response, Int. J. Numer. Methods Engng, Vol 5, pp 503-515.

Kie, T.T., 1986, Hypothesis on rockbursts, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 515-522.

Kim, K., Dischler, S.A., Aggson, J.R., Hardy, M.P., 1986, Characterisation of the state of in situ stress by hydraulic fracturing for a nuclear waste repository in basalt, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 657-668.

Kim, K., Franklin, J.A., 1987, International Society for Rock Mechanics Commission on Testing Methods, Suggested Methods for Rock Stress Determination, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 24, No 1, pp 53-73.

Kim, K., Smith, C.C. 1980, Hydraulic fracturing stress measurements near the Keweenaw Fault in upper Michigan, *Underground Rock Engineering, Proc. 13th Canadian Symp. on Rock Mechanics*, University of Toronto, pp 24-30.

Kirsten, H.A.D., 1976a, Selected Aspects of Rock Stress Measurements in South Africa, *Proceedings of the Symposium on Exploration for Rock Engineering*, Johannesburg, November 1976, pp 55-65.

Kirsten, H.A.D., 1976b, Determination of Rock Mass Elastic Moduli by Back Analysis of Deformation Measurements, *Proceedings of the Symposium for Rock Engineering*, Johannesburg, November 1976, pp 165-172.

Klein, R.J., Barr, M.V., 1986, Regional State of Stress in Western Europe, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 33-44.

Kletzel, G., Tkatchev, V. and Lebedev, J., 1983, Practice of Measurements of Stressed State of Rock Mass by Means of a Multicomponent Dilatometer, *International Symposium on Field Measurements in Geomechanics Zurich*, September 5-8, 1983, pp 187-196.

Kohlbeck, F., Roch, K.H., Scheidegger, A.E., 1980, In Situ Stress Measurements in Austria, *Rock Mechanics*, Suppl. 9, pp 21-29.

Kohlbeck, F., Scheidegger, A.E., 1986, Low-cost monitoring of strain changes, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 189-197.

Kutter, H.K. 1991, Influence of drilling method on borehole breakouts and core diskings, *Proc. 7th Int. Cong. Int. Soc. Rock Mech.*, Aachen, A.A.Balkema, Vol 3, pp 1659-1664.

Lang, P.A., Everitt, R.A., Thompson, P.M., 1986, Horizontal in situ stresses versus depth in the Canadian Shield at the underground research laboratory, *Proc. Int.*

Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 449-456.

Lang, P.A., Thompson, P.M., Nb, L.K.W., 1986, The effect of residual stress and drill holes size on the in situ stress determined by overcoring, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 687-694.

Leeman, E.R. 1964a, Rock Stress Measurements using the trepanning Stress-relieving Technique, Mine and Quarry Engineering, Vol. 3, pp 250-255.

Leeman, E.R., 1964b, The Measurement of Stress in Rock Part I: The Principle of Rock stress Measurements, Journal of the South African Institute of Mining and Metallurgy, Vol. 65, No 2, pp 45-81.

Leeman, E.R., 1964c, The Measurement of Stress in Rock Part II: Borehole Rock Stress Measuring instruments, Journal of the South African Institute of Mining and Metallurgy, Vol 65, No 2, pp 82-114.

Leeman, E.R., 1964d, The Measurement of Stress in Rock Part III: The result of some rock stress investigations, Journal of the South African Institute of Mining and Metallurgy, Vol 65, No 4, pp 254-284.

Leeman, E.R. 1965, Author's reply to discussion on papers by Leeman (1964b, 1964c, 1964d), JI S. Afr. Inst. Min. Metall., Vol 66, pp 109-119.

Leeman, E.R., 1969a, The Measurement of Stress in Rock : A Review of Recent Developments (and a Bibliography), Int. Symp. on the Determination of Stresses in Rock Masses, Lisbon 1969, pp 3-32.

Leeman, E.R., 1969b, The 'Doorstopper' and Triaxial Rock Stress Measuring Instruments Developed by the CSIR, Journal of the South African Institute of Mining and Metallurgy, Vol. 69, No. 7, February 1969, pp 305-339.

Leeman, E.R. and Denkhaus, H.G., 1969, Determination of Stress in Rock with Linear or Non-Linear Elastic Characteristics, *Rock Mechanics* 1, pp 198-206.

Leeman, E.R. and Hayes, D.J., 1966, A Technique for Determining the Complete State of Stress in Rock Using a Single Borehole, *Proc. 1st Int. Cong. Int. Soc. Rock Mech*, Lisbon 1966, Vol. 2, pp 17-24.

Leijon, B.A., 1986, Application of the LUT triaxial overcoring technique in Swedish mines, *Proc. Inst. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 569-582.

Lianjie, W., Chunting, L., Yuanchen, D., Mingyi, O., 1986., The type YG-73 piezomagnetic stress gauge for rock stress measurement, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 227-235.

Lim, H.U., Lee, C., 1986, In-situ stress measurements of rock by stress relief method at some locations in Korea, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 561-568.

Ljunggren, C., Stephansson, O., 1986, Sleeve fracturing - a borehole technique for in-situ determination of rock deformability and rock stress, *Proc. Int. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 323-330.

Ljunggren C, Raillard G, 1987, Rock Stress Measurements by Means of Hydraulic Tests on Pre-existing Fractures at Gidea Test Site, Sweden, *Int. J. Rock Mech. Min. Sci & Geomech. Abstr.* Vol 24, No 6, pp 339-345.

Lu, P.H., 1986, A new method of rock stress measurement with hydraulic borehole pressure cells, *Proc. Inst. Symp. Rock Stress and Rock Stress Measurements*, Stockholm, 1 - 3 September 1986, Centek Publisher, pp 237-245.

Markov, G.A., 1986, Features of tectonic stresses in rock masses and the rational location of openings, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 133-137.

Martin C.D., Christiansson R, 1991, Overcoring in Highly Stressed Granite- the Influence of Microcracking, Int. J. Rock Mech. Min. Sci & Geomech. Abstr., Vol 28, No 1, pp 53-70.

Martin, C.D., Chandler, N.A., 1993, Stress Heterogeneity and Geological Structures, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 30, No 7, pp 993-999.

Martinetti, S., Ribacchi, R., 1980, In Situ Stress Measurements in Italy, Rock Mechanics, Suppl 9, pp 31-47.

Marulanda, A., Ortiz, C., Gutierrez, R., 1986, Definition of the use of steel liners based on hydraulic fracturing tests, A case History, Proc. Inst. Symp. Rock Stress and Rock Stress measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 599-604.

Mao, N., 1986, A new approach for calibration and interpretation of IRAD GAGE vibrating-wire stressmeters, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 499-508.

Matsuki, K., Takeuchi, K., 1993, Three Dimensional *In Situ* Stress Determination by Anelastic Strain Recovery of rock Core, Int. J. Rock Mech. Sci & Geomech. Abstr. Vol 30 No 7, pp 1019-1022.

Mills, K.W., Pender, M.J., 1986, A soft inclusion instrument for in situ stress measurement in coal, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 247-251.

Mills, K.W., Pender, M.J., Depledge, D., 1986, Measurement of in situ stress in coal, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 543-550.

Mizuta, Y., Sano, O., Ogino S., Katoh H., 1987, Three Dimensional Stress Determination by Hydraulic Fracturing for Underground Excavation Design, Int. J. Rock Mech. Min. Sci. & Geomech. Abstr. Vol 24, No 1, pp, 15-29.

Mizuta, Y., Kikuchi, S., Tokunaga, K., 1993, Studies on Hydraulic Fracturing Stress Measurement Assisted by Water Jet Borehole Slotting, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 30, No 7, pp 981-984.

Myrvang, A.M., 1976, Practical Use of Rock Stress Measurements in Norway, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 92-99.

Natau, O., Lempp, CH., Borm, G., 1986, Stress relaxation monitoring by prestressed hard inclusions, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 509-514.

Niewwoudt, A.P.C. and Rozendaal, A., 1990, In Situ Stress Determinations in Mines Located in Two Major Structural Domains in South Africa, Static and Dynamic Considerations in Rock Engineering, Brummer (ed), A.A. Balkema, pp 213-222.

Nishimatsu, Y., Koide, H., Koizumi, S., 1986, On the accuracy and evaluation of rock stress measurements in the Kanto- Tokai region, Japan, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 489-498.

Obert, L. 1939, Measurement of pressures on rock pillars in underground mines, U.S. Bureau of Mines, RI 3444 and RI 3521.

Obert, L. 1967, Determination of stress in rock - a state-of-the-art report, ASTM STP429, Am. Soc. Testing Mats.

Obert, L., Merrill, R.H. and Morgan, T.A. 1962, Borehole deformation gauge for determining the stress in mine rock, U.S. Bureau of Mines, RI 5978.

Odum, J.K., Lee, F.T., Stone, J.W., 1992, Adaptations to Standard Drilling Equipment and Procedures for a USBM Overcore *In Situ* Stress Determination Under Unique Conditions, Int. J. Rock Mech Min. Sci & Geomech. Abstr. Vol 29, No 1, pp 73-76.

Osmanagic, M., Jasarevic, I., 1976, Stresses and Strains Around Underground Openings in Rock with Viscous-Elasto-Plastic Properties, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 107-114.

Ortlepp, W.D. and Bristow, D.M., 1990, Hydro-fracturing and Fluid Injection Data from Simple Tests in Three Different Mining Environments, Static and Dynamic Considerations in Rock Engineering, Brummer (ed), A.A. Balkema, pp 231-240.

Pallister, G.F., Gay, N.C. and Cook, N.G.W., 1970, Measurements of the Virgin State of Stress in Rock at Depth, Proc. 2nd Int. Cong. Int. Soc. Rock Mech, Belgrade 1970, I, 1-5, pp 25-28

Park, D.W., 1986, Development of a new borehole stressmeter and installation tool, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 217-225.

Pahl, A, 1977, In situ stress measurements by overcoring inductive gages, Proc. Int. Symp. on Field Measurements in Rock Mechanics, Zurich, Vol. 1, pp 161-171.

Pinto, J.L., Cunha, A.P., 1986, Rock Stress determination with the STT and SFJ techniques, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 253-260.

Raffield, M.P., James, J.V., Humphreys, I., Isaac, A.K., 1993, Model input parameter selection through instrumentation and back analysis of large excavation failure in a

deep level South African gold mine, Proc. Int. Cong. on Mine Design, Innovative Mine Design for the 21st Century, Kingston, Ontario, ed Bawden and Archibald, Balkema, Rotterdam, pp 641-652.

Rahn, W., 1984, Stress Concentration Factor for the Interpretation of "Doorstopper" Stress Measurements in Anisotropic Rocks, Int. J. Rock Mech. Min. Sci. & Geomech. Abstr. Vol. 21, No. 6 pp. 313-326.

Ribacchi, R. 1977, Rock Stress Measurements in Anisotropic rock masses, International Symposium on Field Measurements in Rock Mechanics - Zurich, April 4-6, 1977, pp 183-196.

Richardson, A.M., Brown, S.M., Hustrulid, W.A., Richardson, D.L., 1986, An interpretation of highly scattered stress measurements in foliated gneiss, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 440-448.

Roberts, A., Hawkes, I., Williams, F.T. and Dhir, R.K., 1964, A Laboratory Study of the Photoelastic Stressmeter, Int. J. Rock Mech. Mining Sci. Vol. 1 pp. 441-457.

Rocha, M., Baptista Lopes, J., Da Silva, J.A. 1966, A new technique for applying the method of the flatjack in determination of stresses inside rock masses, Proc. 1st Int. Cong. Int. Soc. Rock Mech., Lisbon, Vol 2, pp 57-65.

Rocha, M., Silverio, A. 1969, A new method for the complete determination of state of stress in rock masses, Geotechnique, Vol 19, pp 116-132.

Rogiers, J.C., McLennan, J.D. 1982, Factors influencing the initiation orientation of hydraulically induced fractures, Proc. Workshop on Hydraulic Fracturing Stress Measurements, OFR 82-1075, U.S. Geological Survey, Washington DC, pp 489-502.

Rummel, F., 1986, Stresses and tectonics of the upper continental crust - a review, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 177-187.

Sakurai, S., Shimizu, N., 1986, Initial Stress back analysed from displacements due to underground excavations, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 679-686.

Sakurai, S., 1988, Back Analysis of Measured Displacements in a Shallow Tunnel Excavated in Sandy Materials, Proc. Int. Symp. on Underground Engineering, New Delhi, India, April 1988, Vol. 1, pp 33-43.

Sarda, J.P., Perreau, P.J., Boutéca, M.J., Détienne, J.L., Lassus-Dessus, J., 1989, Estimation des contraintes minimales en place au moyen d'essais de microfracturation et de prefracturation, Rock at Great Depth, Maury & Fourmaintraux, pp 1049-1056.

Savage, W.Z., Amadei, B.P., Swolfs, H.S., 1986, Influence of rock fabric on gravity induced stress, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 99-110.

Schäfer, K., 1980, In Situ Stress Measurements in Libya, Rock Mechanics, Suppl.9, pp 49-61.

Schaller, S., McKay, J., Hargraves, A.J., 1976, Rock Pressure Distribution at Caved Faces at Appin Colliery, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 55-62.

Shimizu, N. and Sakurai, S., 1983, Application of Boundary Element Method for Back Analysis Associated with Tunnelling Problems, Boundary Elements, Proceedings of the Fifth Int. Conf. Hiroshima, Japan, November 1983, Springer-Verlag, pp 645-655.

Schmitt, D.R., Li, Y., 1993, Influence of a Stress Relief Hole's Depth on Induced Displacements: Application in Interferometric Stress Determinations, Int. J. Rock Mech. Min. Sci & Geomech Abstr. Vol 30, No 7, pp 985-988.

Smither C.L., Schmitt D.R., Ahrens T.J., 1988, Analysis and Modelling of Holographic Measurements of *In Situ* Stress, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 25, No 6, pp 353-362.

Spathis A, Truong D, 1987, Analysis of a Biaxial Elastic Inclusion Stressmeter, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 24, No 1, pp 31-39.

Stacey, T.R., 1982, Contribution to the mechanism of core discing, Journal of the South African Institute of Mining and Metallurgy, Vol. 82, No. 9, pp 269-274.

Stepanov, V., Batugin, S. 1967, Assessing the effect of the anisotropy of rocks on the accuracy of stress determination by the relief method, Soviet Min. Sci., Vol 3, pp 312-315.

Stephannson, O., Sarkka, P., Myrvang, A., 1986, State of Stress in Fennoscandia, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm 1 - 3 September 1986, Centek Publishers, pp 21-32.

Stille, H., Fredriksson, A., Larsson, H., 1986, Large silo for waste material in Forsmark, Sweden Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 669-678.

Sugawara, K., Obara, Y., Kaneko, K., Aoki, T., 1986, Hemispherical-ended borehole technique for measurement of absolute rock stress, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 207-216.

Swolfs, H.S., Handin, J., 1976, Dependence of Sonic Velocity on Size and In Situ Stress in a Rock Mass, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 41-43.

Swolfs, H.S., Savage, W.Z., 1986, Topographic modification of in situ stress in extensional and compressional tectonic environments, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 89-98.

Tincelin, M.E. 1952, Mesures des pressions de terrains dans les mines de fer de l'est, Anns Inst. Tech. Batim, Vol 58, pp 972-990.

Van Heerden, W.L., 1976, Practical Application of the CSIR Triaxial Strain Cell for Rock Stress Measurements, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 1-6.

Van Heerden, W.L., 1976, Practical Application of the CSIR Triaxial Strain Cell for Rock Stress Measurements, Proceedings of the Symposium on Exploration for Rock Engineering, Johannesburg, November 1976, A.A. Balkema, pp 189-194.

Vernik, L., Zoback, M.D., 1989, Effects of rock elastic and strength properties in estimation of the state of stress at depth, Rock at Great Depth, ed. Maury & Fourmaintraux, A.A. Balkema, pp 1033-1040.

Vik, G., Tunbridge, L., 1986, Hydraulic fracturing - a simple tool for controlling the safety of unlined high pressure shafts and headrace tunnels, Proc. Inst. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 591-598.

Von Schonfeldt, H., 1970, An Experimental Study of open-hole hydraulic fracturing as a stress measurement method with Particular emphasis on field tests, Technical Report MRD 3-70, 204p.

Walker J.R., Martin C.D., Dzik E.J., 1990, Confidence Intervals for *In Situ* stress Measurements, Int. J. Rock Mech Min. Sci & Geomech. Abstr. Vol 27, No 2, pp 139-141.

- Walton, R.J., Worotnicki, G., 1986, A comparison of three borehole instruments for monitoring the change of rock stress with time, Proc. Int. Symp. Rock Stress and Rock Stress Measurement, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 479-488.
- Wang, Y., Shen, S.S., Cheng, H. 1994, Evolution of the plastic zone near a microfracture: a numerical simulation and its implications on in situ stress measurements, Can. Geotech. J., Vol 31, pp 779-787.
- Wang Y, Wong T.F., 1987, Finite Element Analysis of Two Overcoring Techniques for *In Situ* Stress Measurement, Int. J. Rock Mech. Sci & Geomech. Abstr. Vol 24, No 1, pp 41-52.
- Wareham, B.F., Skipp, V.O. 1974, The use of the flatjack installed in a saw-cut slot in the measurement of in situ stress, Proc. 3rd Int. Cong. Int. Soc. Rock Mech., Denver, Vol 2A, pp 481-488.
- Warpinski N.R., Teufel L.W., 1991, In Situ Stress Measurements at Rainier Mesa, Nevada Test Site - Influence of Topography and Lithology on the Stress Site in Tuff, Int. J. Rock Mech. Min. Sci & Geomech, Abstr. Vol 28 No 2/3, pp 143-161.
- Wiles, T.D., Kaiser, P.K., 1994a, *In Situ* Stress Determination Using the Underexcavation Technique - I. Theory, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 31, No 5, pp 439-446.
- Wiles, T.D., Kaiser, P.K., 1994b, *In Situ* Stress Determination Using the Underexcavation Technique -II. Applications, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol. 31, No 5, pp 447-456.
- Wong, T.F., Walsh, J.B., 1985, A Theoretical Analysis of Tectonic Stress Relief During Overcoring, Int. J. Rock Mech. Min. Sci & Geomech. Abstr. Vol 22, No 3, pp 163-171.

Worotnicki, G., 1993, CSIRO Triaxial Stress Measurement Cell, Chapter 13 in Comprehensive Rock Engineering, Vol. 3, ed J.A.Hudson, Pergamon Press, pp 329-394.

Worotnicki, G., Denham, D., 1976, The State of Stress in the Upper Part of the Earth's Crust in Australia According to Measurements in Mines and Tunnels and from Seismic Observations, Investigation of Stress in Rock, International Society of Rock Mechanics Symposium, 1976, Sydney Australia, pp 71-82.

Worotnicki, G., Walton, R.J. 1976, Triaxial hollow inclusion gauges (CSIRO) for determination of rock stresses in situ, Proc. ISRM Symp. on the Investigation of Stress in Rock - Advances in Stress Measurement, Supplement, Sydney, pp 1-8.

Wu M, Wang H.F., 1988, Influence of Nearby Fractures on Stress Measurements by Hydraulic Fracturing, Int. J. Rock Mech. Sci & Geomech. Abstr., Vol. 25, pp 15-23.

Zoback, M.D., Haimson, B.C. 1982, Status of the hydraulic fracturing method for in situ stress measurements, Proc. 23rd U.S. Symp. on Rock Mechanics, Berkeley, pp 143-156.

Zoback, M.D., Mastin, L., Barton, C., 1986, In-situ stress measurements in deep boreholes using hydraulic fracturing, wellbore breakouts, and stonely wave polarization, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 289-299.

Zoback, M.D., Moos, D., Mastin, L., Anderson, R.N. 1985, Wellbore breakouts and in situ stress, J. Geophys. Res., Vol 90, pp 5523-5530.

Zoback, M.D., Pollard, D.D. 1978, Hydraulic fracture propoagation and the interpretation of pressure-time records for in situ stress determinations, Proc. 19th U.S. Symp. on Rock Mechanics, Stateline, pp 14-23.

Zou, P.L., 1986, On ground stress measurement by borehole deformation method using a pre-pressed multiprobe unit of contact type, Proc. Int. Symp. Rock Stress and Rock Stress Measurements, Stockholm, 1 - 3 September 1986, Centek Publishers, pp 149-156.

Zou, D. and Kaiser, P.K., 1990, Determination of In-Situ Stresses from Excavation-Induced Stress Changes, 1990, Rock Mechanics & Rock Engineering 23, pp 167-184.

APPENDIX A

SIMRAC RESEARCH PROPOSAL

**RELIABLE COST EFFECTIVE TECHNIQUE FOR IN-SITU GROUND
STRESS MEASUREMENTS IN DEEP GOLD MINES**

DEPARTMENT OF MINERAL AND ENERGY AFFAIRS
PROPOSAL FOR A PROJECT TO BE FUNDED IN TERMS OF THE MINERALS ACT
- CONFIDENTIAL -

DMEA REFERENCE NUMBER
GAP 220
(FOR OFFICE USE ONLY)

1. PROJECT SUMMARY

PROJECT TITLE: Reliable cost effective technique for in-situ ground stress measurements in deep gold mines.

PROJECT LEADER: T R Stacey

ORGANIZATION: Steffen, Robertson and Kirsten

ADDRESS: P O Box 55291, NORTHLANDS, 2116

TELEPHONE: ⁽⁰¹¹⁾ 441 1143 TELEFAX: ⁽⁰¹¹⁾ 880 8086 TELEX: 4-89763 SA

PRIMARY OUTPUT¹:
Literature survey of existing methods of in-situ rock stress measurements; evaluation of applicability of existing methods to deep gold mines; feasibility study of potential, reliable, cost effective stress measurement technique.

HOW USED ?²: As a basis for developing a routine method for in-situ stress measurement in the deep gold mines

BY WHOM ?³: Rock mechanics researchers in the first instance, and when the technique is developed into a routine tool, by rock mechanics practitioners.

CRITERIA FOR USE⁴: The primary output is at feasibility level. Further development will be required for the technique to be developed for routine use.

POTENTIAL IMPACT⁵:
In-situ stress is one of the most important inputs for rock mechanics analyses. At present the in-situ stress field is usually "guessed". Good quality in-situ stress data will provide much more reliable analyses, which will enhance the quality of design, and safety.

FUNDING REQUIREMENTS (R 000's)	YEAR 1	YEAR 2	YEAR 3
TOTAL PROJECT COST	67 830		
TOTAL SUPPORT REQUESTED FROM SIMRAC	67 830		

DURATION (YY/MM) 94/01 TO 94/06

SIMRAC SUB-COMMITTEE:

AU/PT	<input checked="" type="checkbox"/>	COAL	<input type="checkbox"/>	OTHER	<input type="checkbox"/>	GENERIC	<input type="checkbox"/>
-------	-------------------------------------	------	--------------------------	-------	--------------------------	---------	--------------------------

TRE

2.4 Methodology⁸

NO. OF ENABLING OUTPUT	STEP NO.	METHODOLOGY TO BE USED TO ACCOMPLISH THE ENABLING OUTPUT (INDICATE STEPS/ACTIVITIES)
1	1	Review abstracting journals for references
	2	Identify references from available publications
	3	Obtain hard copy references through library system
2	4	Review of literature
	5	Preparation of draft literature review document
3	6	From literature review identify potential methods
		for feasibility examination
4	7	Preliminary examination of potential methods and
		elimination of unsuitable methods
	8	Theoretical analyses of chosen method or methods
		(expected to be 3D stress analyses)
	9	Evaluation of results
5	10	Preparation of report document including the literature
		survey, and the results and conclusions from the
		theoretical feasibility study.

Key Facilities and Procedures to be used in the Project
 Steffen, Robertson and Kirsten library, a registered library, with a full-time professional librarian.

TRK

3. FINANCIAL DETAILS⁹

3.1 Financial Summary

	R 000 s		
	YEAR 1	YEAR 2	YEAR 3
Project staff costs (from 3.2)	56 000		
Other costs:			
Operating costs (from 3.3)	3 500		
Capital & plant costs (from 3.4)			
Sub-contracted work (from 3.5)			
Value added tax*	8 330		
Total cost of project	67 830		
Less funding from other sources (from 3.6)			
Support requested from SIMRAC	67 830		

*Only for VAT registered concerns

3.2 Project Staff Costs

NAME AND DESIGNATION	MAN DAYS		
	YEAR 1	YEAR 2	YEAR 3
T R Stacey Director	18		
H A D Kirsten Director	1		
P Lourence Senior Ming Eng	12		
S King Librarian	3		
TOTAL (R 000 s)	56 000		

3.3 Operating Costs (Running)

ACTIVITY/EQUIPMENT (Items above R10 000)	COST (R000s)		
	YEAR 1	YEAR 2	YEAR 3
Literature searches	500		
Computer analysis costs	3 000		
Other miscellaneous items			
TOTAL	3 500		

3.4 Capital and Plant Costs¹⁰

(i) ITEMS TO BE PURCHASED OR DEPRECIATED FOR MORE THAN R10 000 PER ITEM	COST (R000s)		
	YEAR 1	YEAR 2	YEAR 3
None			
Other miscellaneous items			
TOTAL			

TR

4. MOTIVATION

(Provide a clear and quantified motivation or justification for the proposal, as well as the main conclusions of a literature survey and the findings of related local and international research. The motivation should include a synthesis of previous work in the project area, both locally and overseas, why the project is proposed, what the primary output will achieve and a cost benefit analysis, if applicable. Use continuation pages where necessary but in most cases it should be possible to clearly present the key data and arguments in the space provided.)

Many in-situ stress measurement methods have been developed. The most commonly used methods are the doorstopper and triaxial strain cell (developed in South Africa), the CSIRO hollow inclusion cell, and hydrofracturing. The first three in particular have been used in South African mines while use of other methods (hydrofracture, borehole slotter, USBM deformation meter, and possibly others) has been far more limited.

A good understanding of the in-situ stress field is essential for realistic mine design and planning of mining layouts and sequences. Without this good quality boundary information, output from the sophisticated stress analysis programs available may be in error or possibly invalid.

In-situ stress measurement methods used in the mines usually provide a wide variation in values of in-situ stress, with low measurement success rate and poor reliability and repeatability. With mines going deeper these problems are likely to increase as spontaneous fracturing is likely to occur around any opening. Existing methods are therefore likely to be less effective in the future. To provide the data required for design under the future stringent mining conditions, a new approach is likely to be required. This must take into account the accessibility of sites, interference with mining operations, availability of, and requirement for services, and time required for measurements. The proposed research programme will answer these factors in principle.

TR5

5.2 Relevant Experience and Publications (one page for each individual listed in 5.1)

NAME: T R Stacey

Relevant Experience:

1. Hands on experience with CSIR doorstopper and triaxial strain cells in-situ stress measurements.
2. Developed computer programme to calculate 3D state of stress from 3 doorstopper measurements.
3. Involvement in stress measurement programmes, in a supervisory and evaluation position, with doorstopper, CSIRO HI cell, and borehole slotter methods.
4. Involved, at an expert consultant level, with hydrofracture stress measurements and large diameter overcore measurements (in a bored tunnel).
5. Familiarity with literature on all the above methods, as well as other lesser used methods such as borehole deepening, back analysis from measured deformations, flat jacks, and others.

Relevant Publications: (Includes those of H A D Kirsten)

1. Selected aspects of rock stress measurements in South Africa, Proc. Symp. Exploration for Rock Engineering, AA Balkema, 1977, pp 55-65.
2. Slotter stress measurements at Palabora Mine, Interfels News, No. 7, February 1993, pp 15-16.
3. Course of instruction in execution of doorstopper stress measurements for El Teniente Mine, Restricted Report 4071, Steffen, Robertson and Kirsten.
4. Measurement of in-situ stresses at Palabora Mine, Restricted Reports 179447/2 and 179447/5, Steffen, Robertson and Kirsten.

TR5

6. DECLARATION BY THE PROPOSING ORGANIZATION

I, the undersigned, being duly authorized to sign this proposal, herewith declare that:

- The information given in this proposal is true and correct in every particular.
- This Organization has the basic expertise and facilities required for satisfactory completion of the project and will adhere to the program of activities as set out in this proposal.
- The costs quoted are in accordance with the normal practice of this Organization and can be substantiated by audit.

Signed on this 29 day of July 1994 for and behalf of

STEFFEN, ROBERTSON AND KIRSTEN

SIGNATURE:



NAME:

T R STACEY

DESIGNATION:

DIRECTOR

RS