

**Technical Report TR-97/004**

March 1997

RESTRICTED

Technical Report TR-97/004

**Permanent deformation  
and in-depth deflection  
records for selected HVS  
tests**

H L Theyse

Programme	:	Pavement Engineering
Programme Manager	:	F C Rust
Technical Review	:	S V Kekwick

**PREPARED BY  
TRANSPORTEK, CSIR**

PO Box 395

Pretoria 0001

Tel +27 12 841 2905

Fax +27 12 841 3232

**NOTE:**

This document is confidential to TRANSPORTEK  
and may only be distributed with the written  
permission of the Director or his nominee

## DOCUMENT RETRIEVAL PAGE

Report No: TR-97/004

Title: Permanent deformation and in-depth deflection records for selected HVS tests

Author: H L Theyse

Client: STEP	Client Report No:	Date: March 1997	Distribution: Restricted
Project No: TRB29	OE2: 9476		ISBN:

**Abstract:** TRANSPORTEK has been involved in accelerated pavement testing (APT) with a fleet of Heavy Vehicle Simulators (HVSs) over the past two decades. During this period, a vast amount of pavement response and performance data has been accumulated, but these data still need to be utilised to their full potential in a structural pavement design model. A data base of selected HVS tests from which structural design models could be developed therefore had to be established.

This report contains material and processed in-depth deflection and permanent deformation data for a number of past HVS tests sections which were added to the structural design database during the current financial year.

**Keywords:** Pavement structure, pavement materials, in-depth deflection, permanent deformation.

**Proposals for implementation:** The data gathered and included in the pavement structural design data base to date should be used to develop permanent deformation design models for South African road building materials.

Related documents (eg software, interim or other reports, working drawings etc):

## Signatures:



S V Kekwick  
Language editor



S V Kekwick  
Technical Reviewer



F C Rust  
Programme Manager



A van der Merwe  
Info Centre

**NOTE: This document is confidential to Transportek and may only be distributed with the written permission of the Director or his nominee**

## **DISCLAIMER**

The views and opinions expressed in this document are those of the author(s) and do not represent the policy of the Division of Roads and Transport Technology of the CSIR

## TABLE OF CONTENTS

1.	INTRODUCTION .....	1
2.	STRUCTURAL INFORMATION OF PAST HVS SECTIONS .....	3
3.	IN-DEPTH DEFLECTION DATA FOR PAST HVS TESTS .....	5
4.	PERMANENT DEFORMATION DATA FOR PAST HVS TESTS .....	7
5.	RECOMMENDATIONS FOR FUTURE WORK .....	9
6.	REFERENCES .....	10

APPENDIX A STRUCTURAL INFORMATION FOR A NUMBER OF SELECTED HVS TESTS

APPENDIX B IN-DEPTH DEFLECTION DATA FOR A NUMBER OF SELECTED HVS TESTS

APPENDIX C PERMANENT DEFORMATION DATA FOR A NUMBER OF SELECTED HVS TESTS

### LIST OF FIGURES

FIGURE 1: TYPICAL PAVEMENT STRUCTURE INFORMATION SHEET .....	4
FIGURE 2: TYPICAL GRAPHICAL REPRESENTATION OF IN-DEPTH DEFLECTION RESULTS ..	6
FIGURE 3: TYPICAL GRAPHICAL REPRESENTATION OF PERMANENT DEFORMATION RESULTS .....	8

### LIST OF TABLES

Table 1: List of HVS tests with available data. ....	2
--	---

## **1. INTRODUCTION**

---

TRANSPORTEK has been involved in accelerated pavement testing (APT) with a fleet of Heavy Vehicle Simulators (HVSs) over the past two decades. During this period, a vast amount of pavement response and performance data has been accumulated but these data still need to be utilised to their full potential in a structural pavement design model. The development of a data base of selected HVS tests from which structural design models for permanent deformation could be developed was therefore initiated.

HVS test sections included in this data base had to conform to three requirements:

1. The location of the tests sections, wheel load, tyre pressure, pavement material data and instrumentation details had to be known for these sections.
2. In-depth deflection data (Multi Depth Deflectometer, MDD) had to be available with surface deflection data (Road Surface Deflectometer, RSD) optional.
3. In-depth permanent deformation data from the MDD stacks had to be available.

This report contains the material and processed in-depth deflection and permanent deformation data for a number of past HVS tests sections that satisfied the above criteria and which were added to the structural design database during the current financial year. This report does not include the analysis of the data and only serves as a record of the work that has been completed during the current financial year. Subject to the approval of funds, the process will continue in the next financial year with the analysis of the data and determining the exact layer thicknesses and material type of the HVS sections with the aim to develop permanent deformation models for unbound pavement materials.

The HVS sections added to the structural design data base during the current project are all from two sites north-west of Pretoria, namely Bultfontein and Rooiwal. Table 1 contains a list of the test numbers with an indication of the data availability for these sections.

Table 1: List of HVS tests with available data.

HVS test number	Structural information	In-depth deflection data at test wheel loads	In-depth permanent deformation data
274A4	✓	✓	✓
275A4	✓	✓	✓
289A4	✓	No in-depth deflection data could be found for this test.	✓
294A4	✓	Seems as if only 40 kN in-depth deflection data were recorded during the test. No deflection data at the test load of 100 kN could be found.	✓
306A4	✓	✓	✓
309A4	✓	Seems as if only 40 kN in-depth deflection data were recorded during the test. No deflection data at the test load of 150 kN could be found.	✓
338A4	✓	✓	✓
339A4	✓	✓	✓
340A4	✓	✓	✓
346A4	✓	✓	✓
347A4	✓	✓	✓
348A4	✓	✓	✓
349A4	✓	✓	✓

## **2. STRUCTURAL INFORMATION OF PAST HVS SECTIONS**

---

One of the biggest challenges of the current project was to obtain the structural information of the pavements tested by HVS in the past. This includes layer thickness data and material classification to a reasonable depth. In many cases the main objective of the HVS tests was to compare different base layer material types or construction techniques with each other, with the result that a proper description of the full pavement profile was seldom done. In most cases only a material classification of the base and subbase is given, with no mention of the material type and layer thickness for the other layers, not to mention initial and final density and moisture profiles.

It is suggested that a full description of the pavement profile should be mandatory for all future HVS tests including the following:

1. A material classification according to TRH14 of all material layers to depth of 1000 mm accompanied and supported by the necessary laboratory test results.
2. A geological description of all the material layer types to a depth of 1000 mm if available. This does not need to be in much detail.
3. An in-situ density and moisture profile taken to a depth of 600 mm. The density reading may be done with the nuclear strata gauge but moisture samples should be removed and oven dried before the addition of any water during the test (or taken at a point representative of the equilibrium moisture content for the test pavement).
4. DCP tests to a depth of 800 mm.
5. A description of the instrumentation details especially the installation depths for the MDD modules.

Figure 1 shows a typical example of the structural information that has been gathered for this project. Similar sheets for all the sections reported on in this report are contained in Appendix A. The material classification of the pavement layers below subbase is suspect and will be confirmed during future research. A standard form, containing a summary of the data listed under the above points as well as information on the test load, inflation pressure and load repetitions will be developed from Figure 1 for future use.

## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST Nr: 349A4

LOCATION : BULTFONTEIN

TEST LOAD : 70 kN dual wheel

ROAD Nr : P2212

TYRE PRESSURE : 690 kPa

CONTACT PRESSURE :




FIGURE 1: TYPICAL PAVEMENT STRUCTURE INFORMATION SHEET

### **3. IN-DEPTH DEFLECTION DATA FOR PAST HVS TESTS**

---

In order for a specific HVS test to be considered for inclusion in the structural design data base, the in-depth deflection data had to be available at the test wheel load. For some of these HVS tests additional in-depth deflection data were available at wheel loads other than the test wheel load and, in some cases, the deflection data were only available for wheel loads other than the test load. In the first case, the deflection data may be used to back-calculate the stiffness of the pavement layers at different stress levels, thereby quantifying the stress dependency of the different pavement materials. In the latter case, unfortunately, because the deflection measurements at the test wheel load are not available, the stresses and strains that caused the permanent deformation of the different pavement layers, may not be calculated with confidence.

An electronic data base in a spreadsheet format of in-depth deflection at various wheel loads has been created for the HVS sections discussed in this report. To assist in the evaluation of the data, graphical representations such as illustrated in Figure 2 are automatically generated by the data base. Appendix B contains similar results for all the HVS sections included in this report. Two types of graphs are produced per wheel load. Firstly the deflection is plotted against depth and secondly against the number of load repetitions. One such sheet is produced for each MDD stack of the test.

Once validated, these deflection data will be used to back-calculate the stress and strain levels in the various pavement layers under the test wheel load.




FIGURE 2: TYPICAL GRAPHICAL REPRESENTATION OF IN-DEPTH DEFLECTION RESULTS

## 4. PERMANENT DEFORMATION DATA FOR PAST HVS TESTS

---

In addition to the spreadsheet data base of in-depth deflection, the permanent deformation data obtained from each of the MDD modules were also entered in a spreadsheet data base. Figure 3 illustrates the graphical representation of these permanent deformation results as produced by the data base. Appendix C contains similar output from the data base for all the HVS sections included in this report.

The top graph in the left hand column represents the raw in-depth permanent deformation data and the top graph in the right hand column represents the validated data. In some cases a number of obvious outliers had to be removed and in other cases only the permanent deformation for a certain duration of the test was retained for further analysis.

The graph in the middle of the left hand column illustrates the regression functions fitted to the permanent deformation data. The basic form of these regression functions is listed in Equation 1. Wolff<sup>1</sup> illustrated that the function listed in Equation 1 may be fitted to in-depth permanent deformation data with a high degree of accuracy.

$$PD = (mN + a)(1 - e^{-bN}) \quad (1)$$

Where PD = Permanent Deformation (mm)

N = Number of load repetitions

e = Base of the natural logarithm

m, a, b = Regression coefficients

The table to the right of the abovementioned graph contains a summary of the regression and correlation coefficients at various depths in the pavement structure.

The graph in the bottom left-hand corner illustrates the permanent deformation data for the upper three pavement layers expressed as a percentage of the original layer thickness. This relative permanent deformation is calculated by deducting the measured deformation at the bottom of the layer from the measured deformation at the top of the layer and dividing the result by the original layer thickness.

The graph in the bottom right hand corner illustrates the absolute displacement of the bottom three MDD modules therefore representing the total deformation from the level of the MDD module downwards. In addition to the individual data points, the regression functions fitted to the data are also shown.




FIGURE 3: TYPICAL GRAPHICAL REPRESENTATION OF PERMANENT DEFORMATION RESULTS

## **5. RECOMMENDATIONS FOR FUTURE WORK**

---

Because of the lack of pavement structure information for past HVS tests it is suggested that a full description of the pavement profile should be mandatory for all future HVS tests including the following:

1. A material classification of all layers to depth of 1000 mm according to TRH14.
2. A geological description of all the material layers to a depth of 1000 mm if available. This does not need to be in much detail.
3. An in-situ density and moisture profile taken to a depth of 600 mm. This could be done with the nuclear strata gauge.
4. DCP tests to a depth of 800 mm.
5. A description of the instrumentation details especially the installation depths for the MDD modules.

A standard form for recording the above data will be developed for future use.

An attempt should be made to obtain the structural information and DCP profiles for at least the HVS tests listed in this report and in a previous report by Theyse<sup>2</sup>. These data, combined with the in-depth deflection and permanent deformation data in the structural design data base, will create a platform from which several structural design issues may be investigated from a broader base than just one or two HVS tests. The total structural design data base will then include the complete data for 29 HVS tests done in the moderate to wet regions in South-Africa.

The acquisition of this data will also enhance the commercial HVS data base currently under development at TRANSPORTEK.

## **6. REFERENCES**

---

1. WOLFF, H. 1992. **The Elasto-Plastic behaviour of granular pavement layers in South Africa.** Pretoria: Ph D Thesis, University of Pretoria.
2. THEYSE, H.L. 1996. **The structural design of low volume roads.** Pretoria: Division for Roads and Transport Technology, CSIR. (DRTT Technical Report; TR-96/037)

---

---

**APPENDIX A**

---

---

**STRUCTURAL INFORMATION FOR A NUMBER OF SELECTED HVS  
TESTS**

---

## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 274A4


LOCATION : ROOIWAL

TEST LOAD : 40 kN dual wheel

ROAD # : R1932

TYRE PRESSURE : 520 kPa

CONTACT PRESSURE :



## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 275A4


LOCATION : ROOIWAL

TEST LOAD : 40 kN dual wheel

ROAD # : R1932

TYRE PRESSURE : 700 kPa

CONTACT PRESSURE :



- Note:
- 1) PD only fitted from 109 804 to 2 105 910 load repetitions for MDD4
  - 2) PD only fitted from 109 804 to 1 533 249 load repetitions for MDD8
  - 3) PD only fitted from 109 804 to 1 110 626 load repetitions for MDD12

## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 289A4


LOCATION : ROOIWAL

TEST LOAD : 70 kN dual wheel

ROAD # : R1932

TYRE PRESSURE : 700 kPa

CONTACT PRESSURE :



## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 294A4


LOCATION : ROOIWAL

TEST LOAD : 100 kN dual wheel

ROAD # : R1932

TYRE PRESSURE : 700 kPa

CONTACT PRESSURE :



# PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 306A4


LOCATION : BULTFONTEIN

TEST LOAD : 40 kN dual wheel

ROAD # : P2212

TYRE PRESSURE : 700 kPa

CONTACT PRESSURE :



De Beer, 1990

Steyn, 1996

## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 309A4


LOCATION : BULTFONTEIN

TEST LOAD : 150 kN single wheel

ROAD # : P2212

TYRE PRESSURE : 1445 kPa

CONTACT PRESSURE :



De Beer, 1990

Steyn, 1996

## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 338A4


LOCATION : ROOIWAL

TEST LOAD : 150 kN single wheel

ROAD # : R1932

TYRE PRESSURE : 960 kPa

CONTACT PRESSURE :



## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 339A4


LOCATION : BULTFONTEIN

TEST LOAD : 40 kN dual wheel

ROAD # : P2212

TYRE PRESSURE : 690 kPa

CONTACT PRESSURE :



## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 340A4


LOCATION : BULTFONTEIN

TEST LOAD : 70 kN dual wheel

ROAD # : P2212

TYRE PRESSURE : 690 kPa

CONTACT PRESSURE :



## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 346A4


LOCATION : BULTFONTEIN

TEST LOAD : 40 kN dual wheel

ROAD # : P2212

TYRE PRESSURE : 690 kPa

CONTACT PRESSURE :



## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 347A4


LOCATION : BULTFONTEIN

TEST LOAD : 70 kN dual wheel

ROAD # : P2212

TYRE PRESSURE : 690 kPa

CONTACT PRESSURE :



## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 348A4


LOCATION : BULTFONTEIN

TEST LOAD : 40 kN dual wheel

ROAD # : P2212

TYRE PRESSURE : 690 kPa

CONTACT PRESSURE :



## PAVEMENT STRUCTURE AND MDD DEPTHS

HVS TEST #: 349A4


LOCATION : BULTFONTEIN

TEST LOAD : 70 kN dual wheel

ROAD # : P2212

TYRE PRESSURE : 690 kPa

CONTACT PRESSURE :



---

---

**APPENDIX B**

---

---


**IN-DEPTH DEFLECTION DATA FOR A NUMBER OF SELECTED HVS  
TESTS**

---

---


### Section 274A4

MDD4




### Section 274A4

MDD4




### Section 274A4

MDD4




### Section 274A4

MDD4




### Section 274A4







MDD4









### Section 274A4




MDD4




























































### Section 309A4

MDD6




### Section 309A4

MDD6




### Section 309A4

MDD6




### Section 309A4

MDD6




### Section 309A4




MDD6









### Section 309A4




MDD6













### Section 338A4

MDD8




### Section 338A4

MDD8




### Section 338A4

MDD8




### Section 338A4

MDD8




### Section 338A4




MDD8



### Section 338A4


MDD8






**Section 338A4**


MDD8

**Section 338A4**


MDD8

**Section 338A4**


MDD8

**Section 338A4**


MDD8




**Section 338A4**




MDD8







**Section 338A4**




MDD8


















































### Section 340A4


MDD12



■ 10	■ 501454
◇ 25000	田 600311
▲ 50000	■ 700278
□ 75000	* 794169
◊ 100000	+ 900103
△ 149200	* 1097861
● 199300	■ 1300111
★ 251011	□ 1400124
▼ 298500	■ 1500645
⊖ 344550	* 1600255
☆ 394240	- 1700066
▽ 453553	△ 199300


### Section 340A4

MDD12



### Section 340A4


MDD12



■ 25000	■ 600311
◇ 50000	田 700278
▲ 75000	* 794169
□ 100000	+ 900103
◊ 149200	+ 1000049
△ 199300	* 1097861
● 251011	■ 1197851
★ 298500	□ 1300111
▼ 344550	■ 1400124
⊖ 394240	* 1500645
☆ 453553	△ 1600255
▽ 501454	● 199300


### Section 340A4

MDD12



### Section 340A4


MDD12









■ 10	■ 550275
◇ 25049	田 598022
▲ 50005	■ 701040
□ 100580	* 749243
◊ 150134	+ 800215
△ 200061	* 848785
● 250000	■ 900573
★ 300240	□ 948103
▼ 346025	■ 1000187
⊖ 399722	* 1046413
☆ 450358	△ 1149899
▽ 500091	● 199300




### Section 340A4




MDD12



























### Section 349A4


MDD8



■ 10	■ 550275
◇ 25049	田 598022
▲ 50005	■ 701040
□ 100580	× 749243
◊ 150134	+ 800215
△ 200061	* 848785
● 250000	■ 900573
★ 300240	□ 1000187
▼ 346025	■ 1046413
⊖ 399722	× 1149899
☆ 450358	— 1248312
▽ 500091	


### Section 349A4

MDD8



### Section 349A4


MDD8



■ 10	■ 550275
◇ 25049	田 598022
▲ 50005	■ 701040
□ 100580	× 749243
◊ 150134	+ 800215
△ 200061	* 848785
● 250000	■ 900573
★ 300240	□ 948103
▼ 346025	■ 1000187
⊖ 399722	× 1046413
☆ 450358	— 1149899
▽ 500091	


### Section 349A4

MDD8



### Section 349A4


MDD8



■ 10	■ 550275
◇ 25049	田 598022
▲ 50005	■ 701040
□ 100580	× 749243
◊ 150134	+ 800215
△ 200061	* 848785
● 250000	■ 900573
★ 300240	□ 948103
▼ 346025	■ 1000187
⊖ 399722	× 1046413
☆ 450358	— 1149899
▽ 500091	


### Section 349A4

MDD8



### Section 349A4


MDD12



■ 10	■ 550275
◇ 25049	■ 598022
▲ 50005	■ 701040
□ 100580	× 749243
◊ 150134	+ 800215
△ 200061	* 848785
● 250000	■ 900573
★ 300240	□ 1000187
▼ 346025	■ 1046413
⊖ 399722	× 1149899
☆ 450358	- 1248312
□ 500091	


### Section 349A4

MDD12



### Section 349A4


MDD12



■ 10	■ 550275
◇ 25049	■ 598022
▲ 50005	■ 701040
□ 100580	× 749243
◊ 150134	+ 800215
△ 200061	* 848785
● 250000	■ 900573
★ 300240	□ 948103
▼ 346025	■ 1000187
⊖ 399722	× 1046413
☆ 450358	- 1149899
□ 500091	


### Section 349A4

MDD12



### Section 349A4


MDD12



■ 10	■ 550275
◇ 25049	■ 598022
▲ 50005	■ 701040
□ 100580	× 749243
◊ 150134	+ 800215
△ 200061	* 848785
● 250000	■ 900573
★ 300240	□ 948103
▼ 346025	■ 1000187
⊖ 399722	× 1046413
☆ 450358	- 1149899
□ 500091	

### Section 349A4

MDD12





---

---

**APPENDIX C**



**PERMANENT DEFORMATION DATA FOR A NUMBER OF  
SELECTED HVS TESTS**



---



**SECTION 274A4 , MDD 4**



Regression coefficients				
Level	a	b	m	Correlation
0 mm	0	0.00E+00	0.00E+00	0.00000
180 mm	0.25	7.00E-06	7.20E-07	0.96506
330 mm	0.05	2.00E-05	2.50E-07	0.95253
480 mm	0	0.00E+00	0.00E+00	0.00000
630 mm	0	0.00E+00	0.00E+00	0.00000







**SECTION 274A4 , MDD 8**



Level	Regression coefficients			
	a	b	m	Correlation
0 mm	0	0.00E+00	0.00E+00	0.00000
180 mm	0.06	5.00E-05	6.50E-07	0.98818
330 mm	0.1	1.50E-05	2.10E-07	0.98438
480 mm	0	0.00E+00	0.00E+00	0.00000
630 mm	0.025	1.20E-05	6.00E-08	0.97612







**SECTION 274A4 , MDD 12**



Level	Regression coefficients			
	a	b	m	Correlation
65 mm	0	0.00E+00	0.00E+00	0.00000
215 mm	0.1	1.20E-05	5.50E-07	0.97376
420 mm	0.08	7.00E-06	2.55E-07	0.93506
630 mm	0	0.00E+00	0.00E+00	0.00000
0	0	0.00E+00	0.00E+00	0.00000







**SECTION 275A4 , MDD 4**



Level	Regression coefficients			
	a	b	m	Correlation
0 mm	0	0.00E+00	0.00E+00	0.00000
180 mm	0.7	4.00E-06	5.50E-07	0.98412
330 mm	0.4	4.00E-06	3.80E-07	0.96252
480 mm	0.31	4.00E-06	3.50E-07	0.93874
630 mm	0.11	4.00E-06	1.50E-07	0.79846







**SECTION 275A4 , MDD 8**



Regression coefficients				
Level	a	b	m	Correlation
0 mm	0	0.00E+00	0.00E+00	0.00000
180 mm	0.45	5.00E-06	4.80E-07	0.93971
330 mm	0.18	2.00E-05	4.20E-07	0.98711
480 mm	0.22	7.00E-06	3.00E-07	0.98618
630 mm	0.04	9.00E-06	1.60E-07	0.95824











**SECTION 275A4 , MDD 12**

Regression coefficients				
Level	a	b	m	Correlation
65 mm	0.61	1.18E-05	1.79E-06	0.99191
215 mm	0.4	1.04E-05	9.00E-07	0.98623
420 mm	0.3	5.00E-06	5.50E-07	0.98514
630 mm	0.19	5.00E-06	1.50E-07	0.83351
0	0	0.00E+00	0.00E+00	0.00000







**SECTION 289A4 , MDD 8**  
Raw permanent deformation data



**SECTION 289A4 , MDD 8**  
Validated permanent deformation data




**SECTION 289A4 , MDD 8**  
Permanent deformation regression functions




**SECTION 289A4 , MDD 8**



Regression coefficients				
Level	a	b	m	Correlation
65mm	1.4	2.32E-05	7.84E-06	0.99177
185mm	0.96	1.42E-05	3.19E-06	0.97416
480mm	0.54	4.40E-06	5.90E-07	0.98770
630mm	0	0.00E+00	0.00E+00	0.00000
0	0	0.00E+00	0.00E+00	0.00000

**SECTION 289A4 , MDD 8**  
Structural layer deformation





**SECTION 289A4 , MDD 8**  
Pavement foundation deformation







SECTION 289A4 , MDD 12


Regression coefficients				
Level	a	b	m	Correlation
65mm	0.6	2.90E-05	3.60E-06	0.59687
185mm	0.4	2.70E-05	2.20E-06	0.57846
480mm	0.3	5.20E-06	6.70E-07	0.98099
630mm	0.21	1.04E-05	4.50E-07	0.93361
0	0	0.00E+00	0.00E+00	0.00000







**SECTION 294A4 , MDD 4**



Regression coefficients				
Level	a	b	m	Correlation
20 mm	1.94	6.00E-06	3.47E-06	0.97548
180 mm	2.2	4.00E-06	2.40E-06	0.98767
330 mm	1.2	3.50E-06	1.00E-06	0.97033
480 mm	0.83	2.80E-06	5.60E-07	0.98579
630 mm	0.09	2.80E-05	7.50E-07	0.89695







**SECTION 294A4 , MDD 8**



Regression coefficients				
Level	a	b	m	Correlation
65 mm	0.65	8.07E-05	7.25E-06	0.99721
185 mm	1.5	5.00E-06	3.00E-06	0.96710
480 mm	0.6	3.50E-06	7.00E-07	0.86022
630 mm	0.33	3.50E-06	3.40E-07	0.66287
0	0	0.00E+00	0.00E+00	0.00000







**SECTION 294A4 , MDD 12**



Regression coefficients				
Level	a	b	m	Correlation
65 mm	0.7	1.00E-05	5.00E-06	0.95067
185 mm	0.48	9.70E-06	2.28E-06	0.99020
480 mm	0.38	5.00E-06	8.50E-07	0.94665
630 mm	0.3	4.00E-06	5.00E-07	0.69214
0	0	0.00E+00	0.00E+00	0.00000







**SECTION 306A4 , MDD 4**



Level	Regression coefficients			
	a	b	m	Correlation
0 mm	1.15	1.30E-05	5.50E-07	0.96202
110 mm	0.84	1.10E-05	3.30E-07	0.97194
310 mm	0.54	1.00E-05	2.10E-07	0.99501
480 mm	0	0.00E+00	0.00E+00	0.00000
0	0	0.00E+00	0.00E+00	0.00000







**SECTION 306A4 , MDD 8**



Regression coefficients				
Level	a	b	m	Correlation
0 mm	1.5	1.30E-05	1.70E-06	0.97905
200 mm	1	1.40E-05	1.30E-06	0.97187
350 mm	0.9	1.30E-05	6.50E-07	0.95671
600 mm	0.38	1.40E-05	1.30E-07	0.80211
0	0	0.00E+00	0.00E+00	0.00000









SECTION 306A4 , MDD 12



Regression coefficients				
Level	a	b	m	Correlation
0 mm	1.58	9.10E-06	1.59E-06	0.99511
110 mm	0.89	9.40E-06	4.60E-07	0.98675
310 mm	0.4	9.40E-06	3.00E-07	0.94923
480 mm	0	0.00E+00	0.00E+00	0.00000
0	0	0.00E+00	0.00E+00	0.00000







Level	Regression coefficients			
	a	b	m	Correlation
20 mm	36	1.80E-04	2.00E-04	0.99485
200 mm	28.2	1.70E-04	1.02E-04	0.99847
350 mm	21.9	1.80E-04	5.30E-05	0.99888
600 mm	10.4	1.50E-04	3.60E-05	0.99803
	0	0.00E+00	0.00E+00	0.00000







SECTION 309A4 , MDD 10


Regression coefficients				
Level	a	b	m	Correlation
110 mm	42	3.00E-04	2.00E-04	0.92009
310 mm	28	1.80E-04	1.14E-04	0.99747
480 mm	22.3	1.80E-04	9.20E-05	0.99532
630 mm	10.6	1.90E-04	5.00E-05	0.98815
	0	0.00E+00	0.00E+00	0.00000







**SECTION 338A4 , MDD 4**



Level	Regression coefficients			
	a	b	m	Correlation
20 mm	15.3	9.00E-05	5.70E-05	0.98323
180 mm	7.7	1.50E-04	2.60E-05	0.97128
330 mm	4.9	1.00E-04	1.20E-05	0.94163
480 mm	1.3	1.30E-04	8.00E-06	0.97940
630 mm	0.65	1.10E-04	5.50E-06	0.94449







SECTION 338A4 , MDD 8



Regression coefficients				
Level	a	b	m	Correlation
20 mm	15	1.30E-04	5.90E-05	0.98313
180 mm	7.6	1.10E-04	2.60E-05	0.97578
330 mm	4.1	1.10E-04	1.40E-05	0.97383
480 mm	1.2	1.00E-04	8.00E-06	0.97845
630 mm	0.75	1.30E-04	6.50E-06	0.97859







SECTION 338A4 , MDD 12



Regression coefficients				
Level	a	b	m	Correlation
20 mm	14.1	1.20E-04	6.00E-05	0.97796
180 mm	7.3	1.30E-04	1.90E-05	0.97010
330 mm	3.5	9.00E-05	1.10E-05	0.96879
480 mm	1.3	7.00E-05	8.00E-06	0.97894
630 mm	0.75	7.00E-05	6.50E-06	0.97473












**SECTION 339A4 , MDD 4**

Regression coefficients				
Level	a	b	m	Correlation
RUT	1.6	1.80E-05	3.50E-07	0.97723
160mm	0.37	4.00E-06	1.30E-07	0.95570
310mm	0.42	2.50E-06	1.00E-07	0.96864
610mm	0.37	2.00E-06	1.00E-07	0.98695
800mm	0.28	2.00E-06	6.50E-08	0.97719














**SECTION 339A4 , MDD 12**

Regression coefficients				
Level	a	b	m	Correlation
RUT	1.7	4.00E-06	3.00E-07	0.91731
160 mm	0.44	1.80E-06	1.30E-07	0.96503
310 mm	0.33	2.80E-06	9.00E-08	0.69478
460 mm	0.2	2.10E-06	5.00E-08	0.93484
610 mm	0	0.00E+00	0.00E+00	0.00000











SECTION 340A4 , MDD 8



Regression coefficients				
Level	a	b	m	Correlation
RUT	0	0.00E+00	0.00E+00	0.00000
90mm	2.73	1.51E-05	2.98E-06	0.99472
260mm	1.2	1.29E-05	1.70E-06	0.99074
460mm	1.2	9.90E-06	1.50E-06	0.98137
800mm	0.2	2.90E-06	1.50E-07	0.51783












SECTION 340A4 , MDD 12

Regression coefficients				
Level	a	b	m	Correlation
RUT	0	0.00E+00	0.00E+00	0.0000
160 mm	1.5	2.00E-05	2.10E-06	0.96503
310 mm	1.4	1.00E-05	1.40E-06	0.97816
460 mm	0.7	1.00E-05	1.05E-06	0.97313
610 mm	0	0.00E+00	0.00E+00	0.00000
















SECTION 346A4, MDD 12

Regression coefficients				
Level	a	b	m	Correlation
PRF	4	5.00E-06	9.00E-07	0.94518
50 mm	3.1	3.00E-06	7.50E-07	0.98848
225 mm	2.35	2.10E-06	4.00E-07	0.99691
385 mm	1.5	2.10E-06	2.50E-07	0.97373
630 mm	0.86	2.60E-06	1.30E-07	0.99337
















**SECTION 347A4, MDD 12**

Regression coefficients				
Level	a	b	m	Correlation
RUT	2.59	3.20E-06	4.20E-07	0.95159
50 mm	1.15	5.60E-06	3.80E-07	0.97129
225 mm	0.85	5.60E-06	3.80E-07	0.98211
385 mm	0.75	5.20E-06	3.20E-07	0.97373
630 mm	0.87	3.20E-06	1.20E-07	0.96374











SECTION 348A4, MDD 8



Level	Regression coefficients			
	a	b	m	Correlation
0mm (R)	0	0.00E+00	0.00E+00	0.00000
0mm	0.23	4.07E-05	5.70E-07	0.97897
170mm	0.33	6.70E-06	3.30E-07	0.98269
415mm	0.25	4.00E-06	3.00E-07	0.98254
585mm	0.18	3.00E-06	9.00E-08	0.95773







**SECTION 348A4, MDD 12**



Regression coefficients				
Level	a	b	m	Correlation
0mm (P)	1.02	1.22E-04	1.50E-06	0.98204
80mm	0.55	7.00E-06	2.50E-07	0.93827
270mm	0.31	7.00E-06	2.00E-07	0.95735
415mm	0.13	9.00E-06	6.00E-08	0.97373
820mm	0.03	6.00E-06	4.00E-08	0.73874







**SECTION 349A4 , MDD 4**



Regression coefficients				
Level	a	b	m	Correlation
0mm (P)	1.4	5.60E-05	1.40E-06	0.95989
80mm	0.8	4.50E-05	1.00E-06	0.97319
270mm	0.5	2.80E-05	8.00E-07	0.96922
415mm	0.5	8.00E-06	6.00E-07	0.98445
820mm	0.1	4.30E-05	9.00E-08	0.50175







**SECTION 349A4 , MDD 8**

Regression coefficients				
Level	a	b	m	Correlation
0mm (P)	1.59	5.08E-05	1.21E-06	0.89960
0mm	0.75	7.22E-05	9.70E-07	0.97956
170mm	0.8	4.00E-06	5.00E-07	0.98715
415mm	0.7	3.00E-06	3.50E-07	0.98826
585mm	0.1	5.00E-06	3.40E-07	0.98087





**SECTION 349A4 , MDD 12**

Regression coefficients				
Level	a	b	m	Correlation
0mm (P)	1.01	3.10E-05	1.70E-06	0.98285
80mm	1.01	6.50E-06	9.00E-07	0.98131
270mm	0.75	5.00E-06	5.00E-07	0.99024
415mm	0.65	4.00E-06	4.50E-07	0.98096
820mm	0.1	1.19E-04	1.10E-07	0.56373

