Monitoring of water resources using satellite information: Applications of MOD16 evapotranspiration

Nebo Jovanovic¹, Richard DH Bugan¹, Cesar L Garcia^{2,3}, Ingrid Teich^{2,4}, Carlos Catalini³, Carlos M Garcia Rodriguez^{2,5}, Qiaozhen Mu⁶ and Maosheng Zhao⁷

¹CSIR, Natural Resources and Environment, PO Box 320, 7599 Stellenbosch, South Africa
 ²Consejo Nacional de Investigaciones Científicas y Técnicas (CONICET), Argentina
 ³Universidad Católica de Córdoba, EHCPA, Av. Armada Argentina 3555, Campus Córdoba,
 C.P 5017, Argentina

⁴Estadística y Biometría, Facultad Ciencias Agropecuarias, Av Valparaiso S/N, Campus Univ. Nacional de Córdoba, C.P 5000, Argentina

⁵CETA, Facultad de Ciencias Físicas Exactas y Naturales, Av Filloy S/N, Campus Univ. Nacional de Córdoba, C.P 5000, Argentina

⁶Numerical Terradynamic Simulation Group, College of Forestry and Conservation, University of Montana, 32 Campus Drive, Missoula, MT 59812, USA
⁷Department of Geographical Sciences, University of Maryland, 2181 Samuel J. LeFrak Hall, College Park, MD 20742, USA

ABSTRACT

The paper describes four years of research on development and testing of evapotranspiration (ET) using MOD16 ET satellite-derived data. A slight decreasing trend in MOD16 ET was observed over the last 13 years in all climatic regions except in the Southern part of South Africa (winter rainfall areas). Average ET for the whole country (2000-2012) was estimated to be 303 mm/a or 481.4 x 10⁹ m³/a (14% of potential evapotranspiration and 67% of rainfall), mainly in the form of plant transpiration (53%) and soil evaporation (39%). Assuming an average rainfall of 450 mm/a, and considering current best estimates of runoff (9% of rainfall), groundwater recharge (5%) and water withdrawal (2%), MOD16 ET estimates were about 15% short of the water balance closure in South Africa. The ET algorithm is improved to account for soil water supply limiting conditions and for applications in sustainable management of water resources using hydrological models.